

MySQL 8 3
my.cnf 3
systemd 3
..... 4


```
[Service]
User=mysql
Group=mysql

# Have mysqld write its state to the systemd notify socket
Type=notify

# Disable service start and stop timeout logic of systemd for mysqld
service.
TimeoutSec=0

# Start main service
ExecStart=/app/mysql/bin/mysqld --defaults-file=/etc/my.cnf $MYSQLD_OPTS

# Use this to switch malloc implementation
EnvironmentFile=-/etc/sysconfig/mysql

# Sets open_files_limit
LimitNOFILE = 10000

Restart=on-failure

RestartPreventExitStatus=1

# Set environment variable MYSQLD_PARENT_PID. This is required for restart.
Environment=MYSQLD_PARENT_PID=1

PrivateTmp=false
```

```
chmod 644 /usr/lib/systemd/system/mysqld.service
systemctl enable mysqld.service
```

가 PATH

```
export PATH="/app/mysql/bin:$PATH"
```

- <https://dev.mysql.com/doc/mysql-secure-deployment-guide/8.0/en/secure-deployment-post-install.html#secure-deployment-systemd-startup>

From:

<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:

https://atl.kr/dokuwiki/doku.php/mysql_8_%EA%B8%B0%EB%B3%B8%EC%84%A4%EC%A0%95%EC%82%AC%ED%95%AD?rev=1591589145

Last update: **2020/06/08 04:05**

