

MySQL 8	3
가	4
.....	5

MySQL 8

MySQL 8

caching_sha2_password

가

```
//
this authentication plugin is not supported

Authentication plugin 'caching_sha2_password' cannot be loaded:
```

가

가

mysql 8

caching_sha2_password가

```
mysql> select host, user, plugin, authentication_string,
password_last_changed from user;
+-----+-----+-----+-----+-----+
| host      | user                | plugin                | authentication_string | password_last_changed |
+-----+-----+-----+-----+-----+
| localhost | mysql.infoschema    | caching_sha2_password | $A$005$THISISACOMBINATIONOFINVALIDSALTANDPASSWORDTHATMUSTNEVERBRBEUSED | 2018-09-11 18:20:19 |
| localhost | mysql.session       | caching_sha2_password | $A$005$THISISACOMBINATIONOFINVALIDSALTANDPASSWORDTHATMUSTNEVERBRBEUSED | 2018-09-11 18:20:19 |
| localhost | mysql.sys           | caching_sha2_password | $A$005$THISISACOMBINATIONOFINVALIDSALTANDPASSWORDTHATMUSTNEVERBRBEUSED | 2018-09-11 18:20:19 |
| localhost | root                | caching_sha2_password | $A$005$THISISACOMBINATIONOFINVALIDSALTANDPASSWORDTHATMUSTNEVERBRBEUSED | 2018-09-11 18:20:19 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> ALTER USER 'root'@'localhost' IDENTIFIED WITH mysql_native_password
BY 'MySQL2020!';
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> select host, user, plugin, authentication_string,
password_last_changed from user;
```

host	user	plugin	authentication_string	password_last_changed
localhost	mysql.infoschema	caching_sha2_password	\$A\$005\$THISISACOMBINATIONOFINVALIDSALTANDPASSWORDTHATMUSTNEVERBRBEUSED	2020-02-18 11:10:33
localhost	mysql.session	caching_sha2_password	\$A\$005\$THISISACOMBINATIONOFINVALIDSALTANDPASSWORDTHATMUSTNEVERBRBEUSED	2020-02-18 11:10:33
localhost	mysql.sys	caching_sha2_password	\$A\$005\$THISISACOMBINATIONOFINVALIDSALTANDPASSWORDTHATMUSTNEVERBRBEUSED	2020-02-18 11:10:33
localhost	root	mysql_native_password	*B08327C27D3ECC829D550501D6A06E0496A74F5C	2020-02-18 11:21:26

4 rows in set (0.00 sec)

가

가 caching_sha2_password
mysql_native_password

```
[mysqld]
# Remove leading # to revert to previous value for
default_authentication_plugin,
# this will increase compatibility with older clients. For background, see:
#
https://dev.mysql.com/doc/refman/8.0/en/server-system-variables.html#sysvar\_
```

```
default_authentication_plugin
# default-authentication-plugin=mysql_native_password
default-authentication-plugin=mysql_native_password
```

```
my.cnf                                default-authentication-
plugin=mysql_native_password
가 .
```

- https://dev.mysql.com/doc/refman/8.0/en/server-system-variables.html#sysvar_default_authentication_plugin
- <http://minsql.com/mysql8/C-2-A-authenticationPlugin/>

From:
<https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://at1.kr/dokuwiki/doku.php/mysql_8_%EC%9D%B8%EC%A6%9D_%ED%94%8C%EB%9F%AC%EA%B7%B8%EC%9D%B8_%EC%95%94%ED%98%B8%EB%B0%A9%EC%8B%9D_%EB%B3%80%EA%B2%BD

Last update: 2020/02/18 03:59

