

<b>MySQL 8</b>	<b>ALTER USER</b> .....	3
<b>root</b>	.....	4



# MySQL 8

# ALTER USER

```
MySQL 8 Database . rpm
/var/log/mysqld.log .
```

```
2020-02-18T02:09:43.292948Z 0 [System] [MY-010910] [Server]
/usr/sbin/mysqld: Shutdown complete (mysqld 8.0.19) MySQL Community Server
- GPL.
2020-02-18T02:10:28.573643Z 0 [System] [MY-013169] [Server] /usr/sbin/mysqld
(mysqld 8.0.19) initializing of server in progress as process 25770
2020-02-18T02:10:32.337916Z 5 [Note] [MY-010454] [Server] A temporary
password is generated for root@localhost: wGKhAhrPg1?_
```

wGKhAhrPg1?\_

MySQL Database

```
[root@test7 ~]# mysql -u root -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 9
Server version: 8.0.19

Copyright (c) 2000, 2020, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input
statement.

mysql> use mysql;
ERROR 1820 (HY000): You must reset your password using ALTER USER statement
before executing this statement.
```

가

가

```
mysql> alter user 'root'@'localhost' identified by 'MySQL2020!';
Query OK, 0 rows affected (0.00 sec)
```

. MySQL 8

MySQL 8  
root

1

```
mysql> alter user 'root'@'localhost' IDENTIFIED WITH mysql_native_password
BY 'mysql2020!';
Query OK, 0 rows affected (0.00 sec)
```

## root

```
root      localhost
          host      %
```

가

```
mysql> CREATE USER 'root'@'%' IDENTIFIED BY 'P@ssW0rd';
mysql> GRANT ALL PRIVILEGES ON *.* TO 'root'@'%' WITH GRANT OPTION;
mysql> commit;
mysql> flush privileges;
```

From:  
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:  
[https://atl.kr/dokuwiki/doku.php/mysql\\_8\\_%EC%B5%9C%EC%B4%88\\_%EC%84%A4%EC%B9%98\\_%ED%9B%84\\_alter\\_user](https://atl.kr/dokuwiki/doku.php/mysql_8_%EC%B5%9C%EC%B4%88_%EC%84%A4%EC%B9%98_%ED%9B%84_alter_user)

Last update: 2020/02/18 04:24

