

netplan	3
<i>cloud-init</i>	3
	3

Last netplan_
update: https://atl.kr/dokuwiki/doku.php/netplan_%EC%9D%B8%ED%84%B0%ED%8E%98%EC%9D%B4%EC%8A%A4_%EC%84%A4%EC%A0%95
2025/06/10 -
07:02

netplan

netplan

cloud-init

ISO cloud-init

```
$ apt purge cloud-init  
$ rm -rf /etc/netplan/*
```

eth0, eth1 bond0 VLAN 320

- IP : 172.16.30.123/24
 - GW : 172.16.30.1
 - DNS : 1.1.1.1 8.8.8.8

```
network:
  version: 2
  ethernets:
    eth0: #
      dhcp4: no
      dhcp6: no
      # WakeOnLan: on #           Wake-on-LAN
      # optional: true #
    eth1: #
      dhcp4: no
      dhcp6: no
      # WakeOnLan: on
      # optional: true

  bonds:
    bond0: #
      dhcp4: no
      dhcp6: no
      interfaces: #
        - eth0
        - eth1
    parameters:
      mode: active-backup #       ( : active-backup, balance-rr,
802.3ad)
```

Last update: 2025/06/10 07:02 netplan_ https://atl.kr/dokuwiki/doku.php/netplan_%EC%9D%B8%ED%84%B0%ED%8E%98%EC%9D%B4%EC%8A%A4_%EC%84%A4%EC%A0%95

```
        mii-monitor-interval: 100 # (ms)
        # transmit-hash-policy: layer2+3 # 802.3ad
        # lacp-rate: fast # 802.3ad      LACP      (slow/fast)

vlans:
  bond0.320: # VLAN      ( : bond0.320      vlan320
가  )
  id: 320 # VLAN ID
  link: bond0 # VLAN      (bond0)
  addresses:
    - 172.16.30.123/24 # IP      (CIDR      )
  routes: #      (      )
    - to: default # 0.0.0.0/0 (      IPv4      )
      via: 172.16.30.1 #      IP
      # metric: 100 #
      # on-link: true #
      #      (      )
  )
  nameservers:
    addresses: [1.1.1.1, 8.8.8.8] # DNS
  # dhcp4: no #      IP      DHCP      (      addresses가
      )
  # dhcp6: no
```

```
$ netplan apply
```

From: <https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link: https://atl.kr/dokuwiki/doku.php/netplan_%EC%9D%B8%ED%84%B0%ED%8E%98%EC%9D%B4%EC%8A%A4_%EC%84%A4%EC%A0%95

Last update: 2025/06/10 07:02

