

- Override logging in WildFly/JBoss** 3
 - 1: add-logging-api-dependencies** 3
 - 2: jboss-deployment-structure.xml** 4
 - 4
 - 5

Override logging in WildFly/JBoss

logback

. logback

1. logback add-logging-api-dependencies false
2. jboss-deployment-structure.xml
3. logback slf4j

1: add-logging-api-dependencies

add-logging-api-dependencies

follow CLI

```
/subsystem=logging:write-attribute(name=add-logging-api-dependencies,value=false)
```

CLI

standalone.xml

가

```
<subsystem xmlns="urn:jboss:domain:logging:6.0">
  <add-logging-api-dependencies value="false"/>
  가 --> <!-- <=<=
  <console-handler name="CONSOLE">
    <level name="INFO"/>
    <formatter>
      <named-formatter name="COLOR-PATTERN"/>
    </formatter>
  </console-handler>
  <periodic-rotating-file-handler name="FILE" autoflush="true">
    <formatter>
      <named-formatter name="PATTERN"/>
    </formatter>
    <file relative-to="jboss.server.log.dir" path="server.log"/>
    <suffix value=".yyyy-MM-dd"/>
    <append value="true"/>
  </periodic-rotating-file-handler>
  <logger category="com.arjuna">
    <level name="WARN"/>
  </logger>
  <logger category="io.jaegertracing.Configuration">
    <level name="WARN"/>
  </logger>
  <logger category="org.jboss.as.config">
    <level name="DEBUG"/>
  </logger>
</subsystem>
```

```

    <logger category="sun.rmi">
      <level name="WARN"/>
    </logger>
    <root-logger>
      <level name="INFO"/>
      <handlers>
        <handler name="CONSOLE"/>
        <handler name="FILE"/>
      </handlers>
    </root-logger>
    <formatter name="PATTERN">
      <pattern-formatter pattern="%d{yyyy-MM-dd HH:mm:ss,SSS} %-5p
[%c] (%t) %s%n"/>
    </formatter>
    <formatter name="COLOR-PATTERN">
      <pattern-formatter pattern="%K{level}%d{HH:mm:ss,SSS} %-5p
[%c] (%t) %s%n"/>
    </formatter>
  </subsystem>

```

implicit

가

2: jboss-deployment-structure.xml

jboss-deployment-structure.xml

/META-INF/jboss-deployment-structure.xml

```

<jboss-deployment-structure>
  <deployment>
    <!-- exclude-subsystem prevents a subsystems deployment unit processors
running on a deployment -->
    <!-- which gives basically the same effect as removing the subsystem,
but it only affects single deployment -->
    <exclude-subsystems>
      <subsystem name="logging" />
    </exclude-subsystems>
  </deployment>
</jboss-deployment-structure>

```

- Wildfly / JBoss Application

```

TEST.ear
|--/META-INF/application.xml
|--/META-INF/jboss-deployment-structure.xml

```

| --/TEST.war ==> check this archive file exists

- Spring-Boot logback.xml logback-spring.xml

- <https://stackoverflow.com/questions/21846329/override-logging-in-wildfly>
- <https://access.redhat.com/solutions/4566431>
- <https://coding-start.tistory.com/186>

From:
<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:
https://atl.kr/dokuwiki/doku.php/override_logging_in_wildfly_jboss

Last update: **2019/11/27 12:35**

