

|  |          |
|--|----------|
| <b>Override logging in WildFly/JBoss .....</b> | <b>3</b> |
| <b>1: add-logging-api-dependencies .....</b>   | <b>3</b> |
| <b>2: jboss-deployment-structure.xml .....</b> | <b>4</b> |
| .....  | 4        |
| .....  | 5        |



# Override logging in WildFly/JBoss

logback

. logback

1. logback add-logging-api-dependencies false
2. jboss-deployment-structure.xml
3. logback slf4j

## 1: add-logging-api-dependencies

add-logging-api-dependencies  
follow CLI

```
/subsystem=logging:write-attribute(name=add-logging-api-dependencies,value=false)
```

CLI        standalone.xml

가

```
<subsystem xmlns="urn:jboss:domain:logging:6.0">
    <add-logging-api-dependencies value="false"/>           <!-- <=>
    가 -->
        <console-handler name="CONSOLE">
            <level name="INFO"/>
            <formatter>
                <named-formatter name="COLOR-PATTERN"/>
            </formatter>
        </console-handler>
        <periodic-rotating-file-handler name="FILE" autoflush="true">
            <formatter>
                <named-formatter name="PATTERN"/>
            </formatter>
            <file relative-to="jboss.server.log.dir" path="server.log"/>
            <suffix value=".yyyy-MM-dd"/>
            <append value="true"/>
        </periodic-rotating-file-handler>
        <logger category="com.arjuna">
            <level name="WARN"/>
        </logger>
        <logger category="io.jaegertracing.Configuration">
            <level name="WARN"/>
        </logger>
        <logger category="org.jboss.as.config">
            <level name="DEBUG"/>
        </logger>
    </subsystem>
```

```

<logger category="sun.rmi">
    <level name="WARN"/>
</logger>
<root-logger>
    <level name="INFO"/>
    <handlers>
        <handler name="CONSOLE"/>
        <handler name="FILE"/>
    </handlers>
</root-logger>
<formatter name="PATTERN">
    <pattern-formatter pattern="%d{yyyy-MM-dd HH:mm:ss,SSS} %-5p
[%c] (%t) %s%e%n"/>
</formatter>
<formatter name="COLOR-PATTERN">
    <pattern-formatter pattern="%K{level}%d{HH:mm:ss,SSS} %-5p
[%c] (%t) %s%e%n"/>
</formatter>
</subsystem>

```

implicit 가 .

## 2: jboss-deployment-structure.xml

jboss-deployment-structure.xml

/META-INF/jboss-deployment-structure.xml

```

<jboss-deployment-structure>
    <deployment>
        <!-- exclude-subsystem prevents a subsystems deployment unit processors
running on a deployment -->
        <!-- which gives basically the same effect as removing the subsystem,
but it only affects single deployment -->
        <exclude-subsystems>
            <subsystem name="logging" />
        </exclude-subsystems>
    </deployment>
</jboss-deployment-structure>

```

- Wildfly / JBoss Application

```

TEST.ear
| --/META-INF/application.xml
| --/META-INF/jboss-deployment-structure.xml

```

| --/TEST.war ==> check this archive file exists

- Spring-Boot                    logback.xml                    logback-spring.xml

- <https://stackoverflow.com/questions/21846329/override-logging-in-wildfly>
- <https://access.redhat.com/solutions/4566431>
- <https://coding-start.tistory.com/186>

From:  
<https://atl.kr/dokuwiki/> - AllThatLinux!



Permanent link:  
[https://atl.kr/dokuwiki/doku.php/override\\_logging\\_in\\_wildfly\\_jboss](https://atl.kr/dokuwiki/doku.php/override_logging_in_wildfly_jboss)

Last update: **2019/11/27 12:35**