

- Override logging in WildFly/JBoss** 3
- add-logging-api-dependencies* 3
- jboss-deployment-structure.xml* 4
- 4
- 5

Override logging in WildFly/JBoss

logback

. logback

- logback add-logging-api-dependencies false
- jboss-deployment-structure.xml
- logback slf4j

add-logging-api-dependencies

add-logging-api-dependencies
follow CLI

```
/subsystem=logging:write-attribute(name=add-logging-api-dependencies,value=false)
```

CLI

standalone.xml

가

```
<subsystem xmlns="urn:jboss:domain:logging:6.0">
  <add-logging-api-dependencies value="false"/>
  <!-- <=>
  가 -->
  <console-handler name="CONSOLE">
    <level name="INFO"/>
    <formatter>
      <named-formatter name="COLOR-PATTERN"/>
    </formatter>
  </console-handler>
  <periodic-rotating-file-handler name="FILE" autoflush="true">
    <formatter>
      <named-formatter name="PATTERN"/>
    </formatter>
    <file relative-to="jboss.server.log.dir" path="server.log"/>
    <suffix value=".yyyy-MM-dd"/>
    <append value="true"/>
  </periodic-rotating-file-handler>
  <logger category="com.arjuna">
    <level name="WARN"/>
  </logger>
  <logger category="io.jaegertracing.Configuration">
    <level name="WARN"/>
  </logger>
  <logger category="org.jboss.as.config">
    <level name="DEBUG"/>
  </logger>
</subsystem>
```

```
<logger category="sun.rmi">
  <level name="WARN"/>
</logger>
<root-logger>
  <level name="INFO"/>
  <handlers>
    <handler name="CONSOLE"/>
    <handler name="FILE"/>
  </handlers>
</root-logger>
<formatter name="PATTERN">
  <pattern-formatter pattern="%d{yyyy-MM-dd HH:mm:ss,SSS} %-5p
[%c] (%t) %s%n"/>
</formatter>
<formatter name="COLOR-PATTERN">
  <pattern-formatter pattern="%K{level}%d{HH:mm:ss,SSS} %-5p
[%c] (%t) %s%n"/>
</formatter>
</subsystem>
```

implicit

가

jboss-deployment-structure.xml

jboss-deployment-structure.xml

/META-INF/jboss-deployment-structure.xml

```
<jboss-deployment-structure>
  <deployment>
    <!-- exclude-subsystem prevents a subsystems deployment unit processors
running on a deployment -->
    <!-- which gives basically the same effect as removing the subsystem,
but it only affects single deployment -->
    <exclude-subsystems>
      <subsystem name="logging" />
    </exclude-subsystems>
  </deployment>
</jboss-deployment-structure>
```

Wildfly / JBoss Application

```
TEST.ear
|--/META-INF/application.xml
```

```
| --/META-INF/jboss-deployment-structure.xml  
|--/TEST.war ==> check this archive file exists
```

- <https://stackoverflow.com/questions/21846329/override-logging-in-wildfly>
- <https://access.redhat.com/solutions/4566431>

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/override_logging_in_wildfly_jboss?rev=1574857772

Last update: **2019/11/27 12:29**

