

Proxy

Client Real IP

..... 3

Proxy

Client Real IP

Proxy / WEB

L4

Client IP request.getRemoteAddr()

IP 가

IP

가

.

server.xml RemoteIpValve

.

```
<Host name="localhost" appBase="webapps"
      unpackWARs="true" autoDeploy="true">

  <!-- [ 가]        IP        RemoteIpValve -->
  <Valve className="org.apache.catalina.valves.RemoteIpValve"
        internalProxies="192\.168\.0\.5"
        remoteIpHeader="x-forwarded-for"
        proxiesHeader="x-forwarded-by"
        protocolHeader="x-forwarded-proto" />

  <!-- [        ] AccessLogValve (        %h        %a가        IP        ) -->
  <Valve className="org.apache.catalina.valves.AccessLogValve"
        directory="logs"
        prefix="localhost_access_log" suffix=".txt"
        pattern="%h %l %u %t &quot;%r&quot; %s %b" />

</Host>
```

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/proxy_%EC%82%AC%EC%9A%A9%EC%8B%9C_client_real_ip_%EA%B8%B0%EB%A1%9D_%EC%84%A4%EC%A0%95?rev=1788877657

Last update: 2026/09/08 14:27

