

1.

```
defaults {
    find_multipaths yes
    user_friendly_names yes
}

# make your luns to human readable name
multipaths {
    multipath {
        wwid          360002ac0000000000000000020000f8cc
        alias          lunlg001
    }
    multipath {
        wwid          360002ac0000000000000000030000f8cc
        alias          lunlg002
    }
}
```

2. LUN RAW Device

/etc/udev/rules.d/60-raw.rules

```
# RAW Device          rawN          N > 0          .
ACTION=="add|change", ENV{DM_NAME}=="lunlg001", RUN+="/bin/raw /dev/raw/raw1
%N"
ACTION=="add|change", ENV{DM_NAME}=="lunlg002", RUN+="/bin/raw /dev/raw/raw2
%N"
```

3. 가 . /etc/udev/rules.d/12-dm-permission.rules

```
ENV{DM_UUID}=="mpath-?*", OWNER:="oracle", GROUP:="dba", MODE:="660"
```

4. RAW Device Oracle RAC .

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/raw_device_%EC%83%9D%EC%84%B1_%EB%B0%A9%EB%B2%95?rev=1423532313

Last update: 2015/06/18 15:49

