


```
yum install rear
```

ReaR /etc/rear/local.conf .

```
$vim /etc/rear/local.conf
OUTPUT=ISO # OUTPUT : BOOT ISO
OUTPUT_URL=nfs://10.32.0.65/rear # OUTPUT_URL : BOOT ISO
BACKUP=NETFS # BACKUP : BACKUP DATA
. (NETFS network filesystem . NFS)
BACKUP_URL=nfs://10.32.0.65/rear # BACKUP_URL : BACKUP DATA가 NFS
```

BACKUP

```
$ rear -d -v mkrescue
```

cron /etc/crontab 가 .

```
$ vim /etc/crontab
# 22:00
0 22 * * 1-5 root /usr/sbin/rear mkrescue
```

ISO . (DVD or KVM)

Recover rhel8 .

가

```
RESCUE rhel8:~ #_
```

```
RESCUE rhel8:~ # ip a add 10.32.0.60/24 dev enp1s0
RESCUE rhel8:~ # ip link set enp1s0 up
RESCUE rhel8:~ # ip a
```

nfs server rear -v recover .

```
RESCUE rhel8:~ # rear -v recover
```

가 가 .

:

https://access.redhat.com/documentation/ko-kr/red_hat_enterprise_linux/7/html/system_administrator_s_guide/ch-relax-and-recover_rear

From:

<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:

<https://atl.kr/dokuwiki/doku.php/rear?rev=1699599842>

Last update: **2023/11/10 07:04**

