Red Hat Identity Management

Red Hat Identity Management

IdM

IDM (Red Hat Identity Management)   Linux   Linux   ID
    ,   ,   , Kerberos   DNS
                    . IdM   RHEL   .
            Kerberos   DNS
                    .

        IdM   IdM   . Red Hat
        ,   .
    .

IdM   RAM   .
RAM   .

- ●   10,000   100   IdM   3GB RAM   1GB
        .
- ●   100,000   50,000   16GB RAM   4GB
        .

                                    10KB   .
                                        .

```
[root@demo ~]#firewall-cmd --add-service=freeipa-ldap --permanent
[root@demo ~]#firewall-cmd --add-service=freeipa-ldaps --permanent
[root@demo ~]#firewall-cmd --add-service=dns --permanent
```

idM

```
[root@demo ~]#yum install ipa-server ipa-server-dns
```

- ●

```
[root@idm ~]#ipa-server-install --realm LAB.EXAMPLE.NET \--ds-password
```

```
RedHat123^ --admin-password RedHat123^ \--setup-dns --no-forwarders --
mkhomedir \--reverse-zone=250.25.172.in-addr.arpa.
```

IdM

IdM   IdM
                    DNS   .

- IdM   (IdM   )   ipa server-del
                            IdM   .

```
[root@server1 ~]#ipa server-del demo.example.net
```

- IdM   (demo.example.net)   ipa-server-install –uninstall   .

```
[root@demo ~]#ipa-server-install --uninstall
```

-          DNS   IdM   (NS) DNS   .

       .

> IdM   IdM
>
>   . Firefox
>
>   .