

RedHat - Undercloud	3
<i>overcloud</i>	3
<i>Undercloud</i>	3
	4

RedHat - Undercloud

overcloud

RedHat - Overcloud

overcloud

- OSP 13, 10

```
heat stack-list
heat stack-delete <UUID>
openstack overcloud plan delete overcloud
```

- OSP 16

```
openstack overcloud delete <overcloud stack name>
```

- overcloud ironic node

```
openstack baremetal node delete $(openstack baremetal node list -f value -c
UUID)
```

Undercloud

```
source stackrc
if [[ $(grep -oP " [0-9]+" /etc/rhosp-release) -ge 16 ]]; then
    echo "OSP16+ deleting overcloud and containers";
    openstack overcloud delete overcloud -y
    sudo podman rm -f $(sudo podman ps -aq)
    sudo podman rmi $(sudo podman images -q)
fi
rm /home/stack/undercloud-passwords.conf
systemctl list-unit-files | grep openstack | awk '{print $1}' | xargs -I {} sudo systemctl stop {}
systemctl list-unit-files | grep neutron | awk '{print $1}' | xargs -I {} sudo systemctl stop {}
sudo systemctl stop docker
sudo systemctl stop podman
sudo systemctl stop keepalived
sudo rm -rf /var/lib/mysql /var/lib/rabbitmq /etc/keystone
/opt/stack/.undercloud-setup /root/stackrc /home/stack/stackrc
/var/opt/undercloud-stack /var/lib/ironic-discoverd/discoverd.sqlite
```

```
/var/lib/ironic-inspector/inspector.sqlite /home/stack/.instack
/root/tripleo-undercloud-passwords /var/lib/registry /etc/pki/ca-
trust/source/anchors/cm-local-ca.pem /httpboot/ /tftpboot/ /srv/*
/var/lib/docker /etc/os-net-config/config.json
dirs="ceilometer heat glance horizon ironic ironic-discoverd keystone
neutron nova swift haproxy"; for dir in $dirs; do sudo rm -rf /etc/$dir ;
sudo rm -rf /var/log/$dir ; sudo rm -rf /var/lib/$dir; done
sudo yum remove -y rabbitmq-server mariadb haproxy openvswitch keepalived
$(rpm -qa | grep openstack) python-tripleoclient docker os-collect-config
os-net-config
sudo rm -rf /etc/httpd/conf.d/10*
sudo rm -rf /etc/httpd/conf.d/25*
sudo rm -rf /etc/httpd/conf.d/openstack-tripleo-ui.conf.rpmsave
sudo sed -i '/:3000/d ; :35357/d ; :5000/d ; :8042/d ; :8774/d ;
:/8777/d' /etc/httpd/conf/ports.conf
sudo rm -rf /etc/pki/tls/certs/undercloud*
sudo rm -rf /etc/pki/tls/private/undercloud*
sudo rm -rf /etc/pki/ca-trust/source/anchors/*local*
sudo rm -rf /etc/sysconfig/network-scripts/ifcfg-br-ctlplane
sudo mv /etc/os-net-config/config.json /etc/os-net-config/config.json.orig
sudo sed -i '/ovs/d ; /OVS/d' /etc/sysconfig/network-scripts/ifcfg-eth1
#!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
#!!!! remove all interface configuration which is related to openvswitch
from /etc/sysconfig/network-scripts, e.g. ifcfg-br_int, ifcfg-ovs_system,
ifcfg-brctlplane, etc. roll back the configuration of the local
interface!!!!
#!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
#!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
#!!!! Starting from RHOSP 12 /root/.my.cnf file should also be removed:
sudo rm /root/.my.cnf
#!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
# With containerized undercloud, we also need to delete /var/lib/config-
data/
sudo rm -rf /var/lib/config-data
sudo rm -rf /etc/cloud/
sudo reboot
```

- <https://access.redhat.com/solutions/2210421>

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!



Permanent link:
https://atl.kr/dokuwiki/doku.php/redhat_-_undercloud_%EC%82%AD%EC%A0%9C

Last update: **2021/07/27 06:46**