

- RedHat Openstack 16.1 Installation** ..... 3
- Undercloud** ..... 3
- deploy.sh ..... 3
- render.sh ..... 3
- network\_data.yaml ..... 3
- roles\_data.yaml ..... 4
- undercloud.conf ..... 10
- containers-prepare-parameter.yaml ..... 11
- nodes.json ..... 12
- template** ..... 13
- network-environment.yaml ..... 13
- NIC Config** ..... 14
- controller.yaml ..... 14
- compute.yaml ..... 20



# RedHat Openstack 16.1 Installation

## Undercloud

### deploy.sh

```
#!/bin/bash
source /home/stack/stackrc
date=`date "+%Y-%m-%d-%I%M"`
rm -rf ~/.ssh/known_hosts

time openstack overcloud deploy --templates \
  -n /home/stack/custom/network_data.yaml \
  -r /home/stack/custom/roles_data.yaml \
  -e /home/stack/custom/node-info.yaml \
  -e /home/stack/containers-prepare-parameter.yaml \
  -e /home/stack/custom/predictive_ips.yaml \
  -e /home/stack/custom/hostname_map.yaml \
  -e /home/stack/templates/environments/network-isolation.yaml \
  -e /home/stack/templates/environments/network-environment.yaml \
  -e /home/stack/templates/environments/ceph-ansible/ceph-ansible-external.yaml \
  -e /home/stack/custom/ceph-config.yaml \
  -e /home/stack/custom/custom_env.yaml \
  --ntp-server 192.168.10.1 \
  --log-file /home/stack/overcloud_deploy_${date}.log
```

### render.sh

```
#!/bin/bash
cd /usr/share/openstack-tripleo-heat-templates
./tools/process-templates.py -o ~/templates -n
/home/stack/custom/network_data.yaml -r /home/stack/custom/roles_data.yaml
```

### network\_data.yaml

```
- name: Storage
  vip: true
  vlan: 30
  name_lower: storage
  ip_subnet: '172.16.1.0/24'
  allocation_pools: [{'start': '172.16.1.4', 'end': '172.16.1.250'}]
  mtu: 1500
- name: StorageMgmt
```

```
name_lower: storage_mgmt
vip: true
vlan: 40
ip_subnet: '172.16.3.0/24'
allocation_pools: [{'start': '172.16.3.4', 'end': '172.16.3.250'}]
mtu: 1500
- name: InternalApi
name_lower: internal_api
vip: true
vlan: 20
ip_subnet: '172.16.2.0/24'
allocation_pools: [{'start': '172.16.2.4', 'end': '172.16.2.250'}]
mtu: 1500
- name: Tenant
vip: false # Tenant network does not use VIPs
name_lower: tenant
vlan: 50
ip_subnet: '172.16.0.0/24'
allocation_pools: [{'start': '172.16.0.4', 'end': '172.16.0.250'}]
mtu: 1500
- name: External
vip: true
name_lower: external
ip_subnet: '192.168.0.0/24'
allocation_pools: [{'start': '192.168.0.140', 'end': '192.168.0.149'}]
gateway_ip: '192.168.0.1'
mtu: 1500
```

## roles\_data.yaml

```
openstack overcloud roles generate \
--roles-path /usr/share/openstack-tripleo-heat-templates/roles/ \
-o /home/stack/roles_data.yaml \
Controller Compute ComputeAlt BlockStorage ObjectStorage CephStorage
```

```
#####
###
# File generated by TripleO
#####
###
#####
###
# Role: Controller
#
#####
###
- name: Controller
description: |
```

```
Controller role that has all the controller services loaded and handles
Database, Messaging and Network functions.
CountDefault: 1
tags:
  - primary
  - controller
networks:
  External:
    subnet: external_subnet
  InternalApi:
    subnet: internal_api_subnet
  Storage:
    subnet: storage_subnet
  StorageMgmt:
    subnet: storage_mgmt_subnet
  Tenant:
    subnet: tenant_subnet
# For systems with both IPv4 and IPv6, you may specify a gateway network
for
# each, such as ['ControlPlane', 'External']
default_route_networks: ['External']
HostnameFormatDefault: '%stackname%-controller-%index%'
# Deprecated & backward-compatible values (FIXME: Make parameters
consistent)
# Set uses_deprecated_params to True if any deprecated params are used.
uses_deprecated_params: True
deprecated_param_extraconfig: 'controllerExtraConfig'
deprecated_param_flavor: 'OvercloudControlFlavor'
deprecated_param_image: 'controllerImage'
deprecated_nic_config_name: 'controller.yaml'
update_serial: 1
ServicesDefault:
  - OS::Triple0::Services::Aide
  - OS::Triple0::Services::AodhApi
  - OS::Triple0::Services::AodhEvaluator
  - OS::Triple0::Services::AodhListener
  - OS::Triple0::Services::AodhNotifier
  - OS::Triple0::Services::AuditD
  - OS::Triple0::Services::BarbicanApi
  - OS::Triple0::Services::BarbicanBackendSimpleCrypto
  - OS::Triple0::Services::BarbicanBackendDogtag
  - OS::Triple0::Services::BarbicanBackendKmip
  - OS::Triple0::Services::BarbicanBackendPkcs11Crypto
  - OS::Triple0::Services::BootParams
  - OS::Triple0::Services::CACerts
  - OS::Triple0::Services::CeilometerAgentCentral
  - OS::Triple0::Services::CeilometerAgentNotification
  - OS::Triple0::Services::CephExternal
  - OS::Triple0::Services::CephGrafana
  - OS::Triple0::Services::CephMds
  - OS::Triple0::Services::CephMgr
```

- OS::Triple0::Services::CephMon
- OS::Triple0::Services::CephRbdMirror
- OS::Triple0::Services::CephRgw
- OS::Triple0::Services::CertmongerUser
- OS::Triple0::Services::CinderApi
- OS::Triple0::Services::CinderBackendDellPs
- OS::Triple0::Services::CinderBackendDellSc
- OS::Triple0::Services::CinderBackendDelleMCPowerFlex
- OS::Triple0::Services::CinderBackendDelleMCPowermax
- OS::Triple0::Services::CinderBackendDelleMCPowerStore
- OS::Triple0::Services::CinderBackendDelleMCSsc
- OS::Triple0::Services::CinderBackendDelleMCUnity
- OS::Triple0::Services::CinderBackendDelleMCMAXISCSI
- OS::Triple0::Services::CinderBackendDelleMCMVNX
- OS::Triple0::Services::CinderBackendDelleMCMVxFlexOS
- OS::Triple0::Services::CinderBackendDelleMCMXtremio
- OS::Triple0::Services::CinderBackendDelleMCMXTREMIIOISCSI
- OS::Triple0::Services::CinderBackendNetApp
- OS::Triple0::Services::CinderBackendPure
- OS::Triple0::Services::CinderBackendScaleIO
- OS::Triple0::Services::CinderBackendVRTSHyperScale
- OS::Triple0::Services::CinderBackendNVMeOF
- OS::Triple0::Services::CinderBackup
- OS::Triple0::Services::CinderHPELeftHandISCSI
- OS::Triple0::Services::CinderScheduler
- OS::Triple0::Services::CinderVolume
- OS::Triple0::Services::Clustercheck
- OS::Triple0::Services::Collectd
- OS::Triple0::Services::ContainerImagePrepare
- OS::Triple0::Services::DesignateApi
- OS::Triple0::Services::DesignateCentral
- OS::Triple0::Services::DesignateProducer
- OS::Triple0::Services::DesignateWorker
- OS::Triple0::Services::DesignateMDNS
- OS::Triple0::Services::DesignateSink
- OS::Triple0::Services::Docker
- OS::Triple0::Services::Ec2Api
- OS::Triple0::Services::EtcD
- OS::Triple0::Services::ExternalSwiftProxy
- OS::Triple0::Services::GlanceApi
- OS::Triple0::Services::GnocchiApi
- OS::Triple0::Services::GnocchiMetricd
- OS::Triple0::Services::GnocchiStatsd
- OS::Triple0::Services::HAproxy
- OS::Triple0::Services::HeatApi
- OS::Triple0::Services::HeatApiCloudwatch
- OS::Triple0::Services::HeatApiCfn
- OS::Triple0::Services::HeatEngine
- OS::Triple0::Services::Horizon
- OS::Triple0::Services::IpaClient

```
- OS::Triple0::Services::Ipsec
- OS::Triple0::Services::IronicApi
- OS::Triple0::Services::IronicConductor
- OS::Triple0::Services::IronicInspector
- OS::Triple0::Services::IronicPxe
- OS::Triple0::Services::IronicNeutronAgent
- OS::Triple0::Services::Iscsid
- OS::Triple0::Services::Keepalived
- OS::Triple0::Services::Kernel
- OS::Triple0::Services::Keystone
- OS::Triple0::Services::LoginDefs
- OS::Triple0::Services::ManilaApi
- OS::Triple0::Services::ManilaBackendCephFs
- OS::Triple0::Services::ManilaBackendIsilon
- OS::Triple0::Services::ManilaBackendNetapp
- OS::Triple0::Services::ManilaBackendUnity
- OS::Triple0::Services::ManilaBackendVNX
- OS::Triple0::Services::ManilaBackendVMAX
- OS::Triple0::Services::ManilaScheduler
- OS::Triple0::Services::ManilaShare
- OS::Triple0::Services::Memcached
- OS::Triple0::Services::MetricsQdr
- OS::Triple0::Services::MistralApi
- OS::Triple0::Services::MistralEngine
- OS::Triple0::Services::MistralExecutor
- OS::Triple0::Services::MistralEventEngine
- OS::Triple0::Services::Multipathd
- OS::Triple0::Services::MySQL
- OS::Triple0::Services::MySQLClient
- OS::Triple0::Services::NeutronApi
- OS::Triple0::Services::NeutronBgpVpnApi
- OS::Triple0::Services::NeutronSfcApi
- OS::Triple0::Services::NeutronCorePlugin
- OS::Triple0::Services::NeutronDhcpAgent
- OS::Triple0::Services::NeutronL2gwAgent
- OS::Triple0::Services::NeutronL2gwApi
- OS::Triple0::Services::NeutronL3Agent
- OS::Triple0::Services::NeutronLinuxbridgeAgent
- OS::Triple0::Services::NeutronMetadataAgent
- OS::Triple0::Services::NeutronML2FujitsuCfab
- OS::Triple0::Services::NeutronML2FujitsuFossw
- OS::Triple0::Services::NeutronOvsAgent
- OS::Triple0::Services::NeutronVppAgent
- OS::Triple0::Services::NeutronAgentsIBConfig
- OS::Triple0::Services::NovaApi
- OS::Triple0::Services::NovaConductor
- OS::Triple0::Services::NovaIronic
- OS::Triple0::Services::NovaMetadata
- OS::Triple0::Services::NovaScheduler
- OS::Triple0::Services::NovaVncProxy
- OS::Triple0::Services::ContainersLogrotateCron
```

- OS::Triple0::Services::OctaviaApi
- OS::Triple0::Services::OctaviaDeploymentConfig
- OS::Triple0::Services::OctaviaHealthManager
- OS::Triple0::Services::OctaviaHousekeeping
- OS::Triple0::Services::OctaviaWorker
- OS::Triple0::Services::OpenStackClients
- OS::Triple0::Services::OVNDBs
- OS::Triple0::Services::OVNController
- OS::Triple0::Services::Pacemaker
- OS::Triple0::Services::PankoApi
- OS::Triple0::Services::PlacementApi
- OS::Triple0::Services::OsloMessagingRpc
- OS::Triple0::Services::OsloMessagingNotify
- OS::Triple0::Services::Podman
- OS::Triple0::Services::Rear
- OS::Triple0::Services::Redis
- OS::Triple0::Services::Rhsm
- OS::Triple0::Services::Rsyslog
- OS::Triple0::Services::RsyslogSidecar
- OS::Triple0::Services::SaharaApi
- OS::Triple0::Services::SaharaEngine
- OS::Triple0::Services::Securetty
- OS::Triple0::Services::Snmpp
- OS::Triple0::Services::Sshd
- OS::Triple0::Services::SwiftProxy
- OS::Triple0::Services::SwiftDispersion
- OS::Triple0::Services::SwiftRingBuilder
- OS::Triple0::Services::SwiftStorage
- OS::Triple0::Services::Timesync
- OS::Triple0::Services::Timezone
- OS::Triple0::Services::TripleoFirewall
- OS::Triple0::Services::TripleoPackages
- OS::Triple0::Services::Tuned
- OS::Triple0::Services::Vpp
- OS::Triple0::Services::Zaqaar

#####

###

# Role: Compute

#

#####

###

```
- name: Compute
  description: |
    Basic Compute Node role
  CountDefault: 1
  # Create external Neutron bridge (unset if using ML2/OVS without DVR)
  tags:
    - external_bridge
  networks:
    InternalApi:
```



```
    subnet: internal_api_subnet
Tenant:
    subnet: tenant_subnet
Storage:
    subnet: storage_subnet
HostnameFormatDefault: '%stackname%-novacompute-%index%'
RoleParametersDefault:
    TunedProfileName: "virtual-host"
# Deprecated & backward-compatible values (FIXME: Make parameters
consistent)
# Set uses_deprecated_params to True if any deprecated params are used.
# These deprecated_params only need to be used for existing roles and not
for
# composable roles.
uses_deprecated_params: True
deprecated_param_image: 'NovaImage'
deprecated_param_extraconfig: 'NovaComputeExtraConfig'
deprecated_param_metadata: 'NovaComputeServerMetadata'
deprecated_param_scheduler_hints: 'NovaComputeSchedulerHints'
deprecated_param_ips: 'NovaComputeIPs'
deprecated_server_resource_name: 'NovaCompute'
deprecated_nic_config_name: 'compute.yaml'
update_serial: 25
ServicesDefault:
- OS::Triple0::Services::Aide
- OS::Triple0::Services::AuditD
- OS::Triple0::Services::BootParams
- OS::Triple0::Services::CACerts
- OS::Triple0::Services::CephClient
- OS::Triple0::Services::CephExternal
- OS::Triple0::Services::CertmongerUser
- OS::Triple0::Services::Collectd
- OS::Triple0::Services::ComputeCeilometerAgent
- OS::Triple0::Services::ComputeNeutronCorePlugin
- OS::Triple0::Services::ComputeNeutronL3Agent
- OS::Triple0::Services::ComputeNeutronMetadataAgent
- OS::Triple0::Services::ComputeNeutronOvsAgent
- OS::Triple0::Services::Docker
- OS::Triple0::Services::IpaClient
- OS::Triple0::Services::Ipsec
- OS::Triple0::Services::Iscsid
- OS::Triple0::Services::Kernel
- OS::Triple0::Services::LoginDefs
- OS::Triple0::Services::MetricsQdr
- OS::Triple0::Services::Multipathd
- OS::Triple0::Services::MySQLClient
- OS::Triple0::Services::NeutronBgpVpnBagpipe
- OS::Triple0::Services::NeutronLinuxbridgeAgent
- OS::Triple0::Services::NeutronVppAgent
- OS::Triple0::Services::NovaAZConfig
- OS::Triple0::Services::NovaCompute
```

- OS::Triple0::Services::NovaLibvirt
- OS::Triple0::Services::NovaLibvirtGuests
- OS::Triple0::Services::NovaMigrationTarget
- OS::Triple0::Services::ContainersLogrotateCron
- OS::Triple0::Services::Podman
- OS::Triple0::Services::Rear
- OS::Triple0::Services::Rhsm
- OS::Triple0::Services::Rsyslog
- OS::Triple0::Services::RsyslogSidecar
- OS::Triple0::Services::Securetty
- OS::Triple0::Services::Snmpp
- OS::Triple0::Services::Sshd
- OS::Triple0::Services::Timesync
- OS::Triple0::Services::Timezone
- OS::Triple0::Services::TripleoFirewall
- OS::Triple0::Services::TripleoPackages
- OS::Triple0::Services::Tuned
- OS::Triple0::Services::Vpp
- OS::Triple0::Services::OVNController
- OS::Triple0::Services::OVNMetadataAgent

## undercloud.conf

```
[DEFAULT]
# /
clean_nodes = true
# ( false)
#cleanup = true
#
container_images_file = /home/stack/containers-prepare-parameter.yaml
#
#container_insecure_registries = registry:5000
# telemetry
enable_telemetry = false
local_interface = enp2s0
local_ip = 192.168.10.1/24
#local_mtu = 1500
local_subnet = ctlplane-subnet
# DNS . CloudDomain

#overcloud_domain_name = cloud.localdomain

subnets = ctlplane-subnet
undercloud_admin_host = 192.168.10.3
undercloud_hostname = director.osp.kepri
undercloud_public_host = 192.168.10.2
undercloud_ntp_servers = 192.168.10.250
undercloud_timezone = 'Asia/Seoul'

[ctlplane-subnet]
```

```
cidr = 192.168.10.0/24
dhcp_end = 192.168.10.249
dhcp_start = 192.168.10.230
gateway = 192.168.10.1
inspection_iprange = 192.168.10.210,192.168.10.229
masquerade = true
```

## containers-prepare-parameter.yaml

```
# Generated with the following on 2022-02-07T15:38:01.717320
#
# openstack tripleo container image prepare default --local-push-
destination --output-env-file containers-prepare-parameter.yaml
#

parameter_defaults:
  ContainerImagePrepare:
    - push_destination: true
      set:
        ceph_alertmanager_image: ose-prometheus-alertmanager
        ceph_alertmanager_namespace: registry.redhat.io/openshift4
        ceph_alertmanager_tag: 4.1
        ceph_grafana_image: rhceph-4-dashboard-rhel8
        ceph_grafana_namespace: registry.redhat.io/rhceph
        ceph_grafana_tag: 4
        ceph_image: rhceph-4-rhel8
        ceph_namespace: registry.redhat.io/rhceph
        ceph_node_exporter_image: ose-prometheus-node-exporter
        ceph_node_exporter_namespace: registry.redhat.io/openshift4
        ceph_node_exporter_tag: v4.1
        ceph_prometheus_image: ose-prometheus
        ceph_prometheus_namespace: registry.redhat.io/openshift4
        ceph_prometheus_tag: 4.1
        ceph_tag: latest
        name_prefix: openstack-
        name_suffix: ''
        namespace: registry.redhat.io/rhosp-rhel8
        neutron_driver: ovn
        rhel_containers: false
        tag: '16.1.7'
        tag_from_label: '{version}-{release}'
  ContainerImageRegistryCredentials:
    registry.redhat.io:
      userid@domain.co.kr: 'password'
  ContainerImageRegistryLogin: true
```

## nodes.json

```
{
  "nodes": [
    {
      "mac": [
        "52:54:00:81:49:42"
      ],
      "name": "control0",
      "pm_type": "pxe_ipmitool",
      "pm_user": "admin",
      "pm_password": "admin",
      "pm_addr": "192.168.0.31",
      "pm_port": "6231",
      "capabilities": "profile:control,boot_option:local"
    },
    {
      "mac": [
        "52:54:00:67:7b:ce"
      ],
      "name": "control1",
      "pm_type": "pxe_ipmitool",
      "pm_user": "admin",
      "pm_password": "admin",
      "pm_addr": "192.168.0.31",
      "pm_port": "6232",
      "capabilities": "profile:control,boot_option:local"
    },
    {
      "mac": [
        "52:54:00:80:ef:db"
      ],
      "name": "control2",
      "pm_type": "pxe_ipmitool",
      "pm_user": "admin",
      "pm_password": "admin",
      "pm_addr": "192.168.0.31",
      "pm_port": "6233",
      "capabilities": "profile:control,boot_option:local"
    },
    {
      "mac": [
        "52:54:00:e0:3b:a6"
      ],
      "name": "compute0",
      "pm_type": "pxe_ipmitool",
      "pm_user": "admin",
      "pm_password": "admin",
      "pm_addr": "192.168.0.31",
      "pm_port": "6234",
    }
  ]
}
```

```
    "capabilities": "profile:compute,boot_option:local"
  },
  {
    "mac": [
      "52:54:00:e7:b0:7b"
    ],
    "name": "compute1",
    "pm_type": "pxe_ipmitool",
    "pm_user": "admin",
    "pm_password": "admin",
    "pm_addr": "192.168.0.31",
    "pm_port": "6235",
    "capabilities": "profile:compute,boot_option:local"
  }
]
}
```

## template

### network-environment.yaml

```
resource_registry:
  OS::Triple0::Controller::Net::SoftwareConfig:
    ../network/config/custom-nic/controller.yaml
  OS::Triple0::Compute::Net::SoftwareConfig:
    ../network/config/custom-nic/compute.yaml
parameter_defaults:
  StorageNetCidr: '172.16.1.0/24'
  StorageAllocationPools: [{'start': '172.16.1.4', 'end': '172.16.1.250'}]
  StorageNetworkVlanID: 30
  StorageMgmtNetCidr: '172.16.3.0/24'
  StorageMgmtAllocationPools: [{'start': '172.16.3.4', 'end':
'172.16.3.250'}]
  StorageMgmtNetworkVlanID: 40
  InternalApiNetCidr: '172.16.2.0/24'
  InternalApiAllocationPools: [{'start': '172.16.2.4', 'end':
'172.16.2.250'}]
  InternalApiNetworkVlanID: 20
  TenantNetCidr: '172.16.0.0/24'
  TenantAllocationPools: [{'start': '172.16.0.4', 'end': '172.16.0.250'}]
  TenantNetworkVlanID: 50
  TenantNetPhysnetMtu: 1500
  ExternalNetCidr: '192.168.0.0/24'
  ExternalAllocationPools: [{'start': '192.168.0.140', 'end':
'192.168.0.149'}]
  ExternalInterfaceDefaultRoute: '192.168.0.1'
  DnsServers: ['8.8.8.8']
  NeutronNetworkType: 'geneve,vlan,flat'
```

```
NeutronNetworkVLANRanges: 'datacentre:1:1000'  
BondInterfaceOptions: "bond_mode=active-backup"  
NeutronEnableDVR: false
```

## NIC Config

### controller.yaml

```
heat_template_version: rocky  
description: >  
  Software Config to drive os-net-config to configure multiple interfaces  
  for the Controller role.  
parameters:  
  ControlPlaneIp:  
    default: ''  
    description: IP address/subnet on the ctlplane network  
    type: string  
  ControlPlaneSubnetCidr:  
    default: ''  
    description: >  
      The subnet CIDR of the control plane network. (The parameter is  
      automatically resolved from the ctlplane subnet's cidr attribute.)  
    type: string  
  ControlPlaneDefaultRoute:  
    default: ''  
    description: The default route of the control plane network. (The  
parameter  
    is automatically resolved from the ctlplane subnet's gateway_ip  
attribute.)  
    type: string  
  ControlPlaneStaticRoutes:  
    default: []  
    description: >  
      Routes for the ctlplane network traffic.  
      JSON route e.g. [{'destination':'10.0.0.0/16', 'nexthop':'10.0.0.1'}]  
      Unless the default is changed, the parameter is automatically resolved  
      from the subnet host_routes attribute.  
    type: json  
  ControlPlaneMtu:  
    default: 1500  
    description: The maximum transmission unit (MTU) size(in bytes) that is  
      guaranteed to pass through the data path of the segments in the  
network.  
      (The parameter is automatically resolved from the ctlplane network's  
mtu attribute.)  
    type: number  
  
  StorageIpSubnet:
```

```
default: ''
description: IP address/subnet on the storage network
type: string
StorageNetworkVlanID:
default: 30
description: Vlan ID for the storage network traffic.
type: number
StorageMtu:
default: 1500
description: The maximum transmission unit (MTU) size(in bytes) that is
  guaranteed to pass through the data path of the segments in the
  Storage network.
type: number
StorageInterfaceRoutes:
default: []
description: >
  Routes for the storage network traffic.
  JSON route e.g. [{'destination':'10.0.0.0/16', 'nexthop':'10.0.0.1'}]
  Unless the default is changed, the parameter is automatically resolved
  from the subnet host_routes attribute.
type: json
StorageMgmtIpSubnet:
default: ''
description: IP address/subnet on the storage_mgmt network
type: string
StorageMgmtNetworkVlanID:
default: 40
description: Vlan ID for the storage_mgmt network traffic.
type: number
StorageMgmtMtu:
default: 1500
description: The maximum transmission unit (MTU) size(in bytes) that is
  guaranteed to pass through the data path of the segments in the
  StorageMgmt network.
type: number
StorageMgmtInterfaceRoutes:
default: []
description: >
  Routes for the storage_mgmt network traffic.
  JSON route e.g. [{'destination':'10.0.0.0/16', 'nexthop':'10.0.0.1'}]
  Unless the default is changed, the parameter is automatically resolved
  from the subnet host_routes attribute.
type: json
InternalApiIpSubnet:
default: ''
description: IP address/subnet on the internal_api network
type: string
InternalApiNetworkVlanID:
default: 20
description: Vlan ID for the internal_api network traffic.
type: number
```

```
InternalApiMtu:
  default: 1500
  description: The maximum transmission unit (MTU) size(in bytes) that is
    guaranteed to pass through the data path of the segments in the
    InternalApi network.
  type: number
InternalApiInterfaceRoutes:
  default: []
  description: >
    Routes for the internal_api network traffic.
    JSON route e.g. [{'destination':'10.0.0.0/16', 'nexthop':'10.0.0.1'}]
    Unless the default is changed, the parameter is automatically resolved
    from the subnet host_routes attribute.
  type: json
TenantIpSubnet:
  default: ''
  description: IP address/subnet on the tenant network
  type: string
TenantNetworkVlanID:
  default: 50
  description: Vlan ID for the tenant network traffic.
  type: number
TenantMtu:
  default: 1500
  description: The maximum transmission unit (MTU) size(in bytes) that is
    guaranteed to pass through the data path of the segments in the
    Tenant network.
  type: number
TenantInterfaceRoutes:
  default: []
  description: >
    Routes for the tenant network traffic.
    JSON route e.g. [{'destination':'10.0.0.0/16', 'nexthop':'10.0.0.1'}]
    Unless the default is changed, the parameter is automatically resolved
    from the subnet host_routes attribute.
  type: json
ExternalIpSubnet:
  default: ''
  description: IP address/subnet on the external network
  type: string
ExternalNetworkVlanID:
  default: 10
  description: Vlan ID for the external network traffic.
  type: number
ExternalMtu:
  default: 1500
  description: The maximum transmission unit (MTU) size(in bytes) that is
    guaranteed to pass through the data path of the segments in the
    External network.
  type: number
```



```

ExternalInterfaceDefaultRoute:
  default: ''
  description: default route for the external network
  type: string
ExternalInterfaceRoutes:
  default: []
  description: >
    Routes for the external network traffic.
    JSON route e.g. [{'destination':'10.0.0.0/16', 'nexthop':'10.0.0.1'}]
    Unless the default is changed, the parameter is automatically resolved
    from the subnet host_routes attribute.
  type: json

DnsServers: # Override this via parameter_defaults
  default: []
  description: >
    DNS servers to use for the Overcloud (2 max for some implementations).
    If not set the nameservers configured in the ctlplane subnet's
    dns_nameservers attribute will be used.
  type: comma_delimited_list
DnsSearchDomains: # Override this via parameter_defaults
  default: []
  description: A list of DNS search domains to be added (in order) to
  resolv.conf.
  type: comma_delimited_list
#####
resources:

  MinViableMtu:
    # This resource resolves the minimum viable MTU for interfaces, bonds
    and
    # bridges that carry multiple VLANs. Each VLAN may have different MTU.
    The
    # bridge, bond or interface must have an MTU to allow the VLAN with the
    # largest MTU.
    type: OS::Heat::Value
    properties:
      type: number
      value:
        yaql:
          expression: $.data.max()
          data:
            - {get_param: ControlPlaneMtu}
            - {get_param: StorageMtu}
            - {get_param: InternalApiMtu}
            - {get_param: TenantMtu}

  OsNetConfigImpl:
    type: OS::Heat::SoftwareConfig
    properties:
      group: script

```

```
config:
  str_replace:
    template:
      get_file: ../../scripts/run-os-net-config.sh
  params:
    $network_config:
      network_config:
```

```
##### Main Interface [Provision]
- type: interface
  name: nic1
  mtu:
    get_param: ControlPlaneMtu
  use_dhcp: false
  dns_servers:
    get_param: DnsServers
  domain:
    get_param: DnsSearchDomains
  addresses:
    - ip_netmask:
        list_join:
          - /
          - - get_param: ControlPlaneIp
            - get_param: ControlPlaneSubnetCidr
  routes:
    list_concat_unique:
      - get_param: ControlPlaneStaticRoutes
```

```
##### Main Interface [VLAN]
- type: ovs_bridge
  name: br-local
  dns_server:
    get_param: DnsServers
  use_dhcp: false
```

```
members:
```

```
##### Sub Interface
- type: interface
  name: nic2
  mtu:
    get_attr: [MinViableMtu, value]
  # force the MAC address of the bridge to this interface
  primary: true
```

```
##### Sub Interface [Storage]
- type: vlan
  mtu:
    get_param: StorageMtu
  vlan_id:
    get_param: StorageNetworkVlanID
```

```

addresses:
  - ip_netmask:
      get_param: StorageIpSubnet
routes:
  list_concat_unique:
    - get_param: StorageInterfaceRoutes
##### Sub Interface [StorageMgmt]
- type: vlan
mtu:
  get_param: StorageMgmtMtu
vlan_id:
  get_param: StorageMgmtNetworkVlanID
addresses:
  - ip_netmask:
      get_param: StorageMgmtIpSubnet
routes:
  list_concat_unique:
    - get_param: StorageMgmtInterfaceRoutes
##### Sub Interface [InternalApi]
- type: vlan
mtu:
  get_param: InternalApiMtu
vlan_id:
  get_param: InternalApiNetworkVlanID
addresses:
  - ip_netmask:
      get_param: InternalApiIpSubnet
routes:
  list_concat_unique:
    - get_param: InternalApiInterfaceRoutes
##### Sub Interface [Tenant]
- type: vlan
mtu:
  get_param: TenantMtu
vlan_id:
  get_param: TenantNetworkVlanID
addresses:
  - ip_netmask:
      get_param: TenantIpSubnet
routes:
  list_concat_unique:
    - get_param: TenantInterfaceRoutes

##### Main Interface [External - NIC]
- type: ovs_bridge
name: bridge_name
mtu:
  get_param: ExternalMtu
dns_servers:
  get_param: DnsServers
use_dhcp: false

```

```
addresses:
- ip_netmask:
  get_param: ExternalIpSubnet
routes:
  list_concat_unique:
  - get_param: ExternalInterfaceRoutes
  - - default: true
    next_hop:
      get_param: ExternalInterfaceDefaultRoute
members:
- type: interface
  name: nic3
  mtu:
    get_param: ExternalMtu
  use_dhcp: false
  primary: true
```

#####

```
outputs:
  OS::stack_id:
    description: The OsNetConfigImpl resource.
    value:
      get_resource: OsNetConfigImpl(undercloud)
```

## compute.yaml

```
heat_template_version: rocky
description: >
  Software Config to drive os-net-config to configure multiple interfaces
  for the Compute role.
parameters:
  ControlPlaneIp:
    default: ''
    description: IP address/subnet on the ctlplane network
    type: string
  ControlPlaneSubnetCidr:
    default: ''
    description: >
      The subnet CIDR of the control plane network. (The parameter is
      automatically resolved from the ctlplane subnet's cidr attribute.)
    type: string
  ControlPlaneDefaultRoute:
    default: ''
    description: The default route of the control plane network. (The
    parameter
      is automatically resolved from the ctlplane subnet's gateway_ip
    attribute.)
    type: string
  ControlPlaneStaticRoutes:
```

```
default: []
description: >
  Routes for the ctlplane network traffic.
  JSON route e.g. [{'destination':'10.0.0.0/16', 'nexthop':'10.0.0.1'}]
  Unless the default is changed, the parameter is automatically resolved
  from the subnet host_routes attribute.
type: json
ControlPlaneMtu:
  default: 1500
  description: The maximum transmission unit (MTU) size(in bytes) that is
    guaranteed to pass through the data path of the segments in the
network.
  (The parameter is automatically resolved from the ctlplane network's
mtu attribute.)
  type: number

StorageIpSubnet:
  default: ''
  description: IP address/subnet on the storage network
  type: string
StorageNetworkVlanID:
  default: 30
  description: Vlan ID for the storage network traffic.
  type: number
StorageMtu:
  default: 1500
  description: The maximum transmission unit (MTU) size(in bytes) that is
    guaranteed to pass through the data path of the segments in the
    Storage network.
  type: number
StorageInterfaceRoutes:
  default: []
  description: >
    Routes for the storage network traffic.
    JSON route e.g. [{'destination':'10.0.0.0/16', 'nexthop':'10.0.0.1'}]
    Unless the default is changed, the parameter is automatically resolved
    from the subnet host_routes attribute.
  type: json
InternalApiIpSubnet:
  default: ''
  description: IP address/subnet on the internal_api network
  type: string
InternalApiNetworkVlanID:
  default: 20
  description: Vlan ID for the internal_api network traffic.
  type: number
InternalApiMtu:
  default: 1500
  description: The maximum transmission unit (MTU) size(in bytes) that is
    guaranteed to pass through the data path of the segments in the
    InternalApi network.
```

```
type: number
InternalApiInterfaceRoutes:
  default: []
  description: >
    Routes for the internal_api network traffic.
    JSON route e.g. [{'destination':'10.0.0.0/16', 'nexthop':'10.0.0.1'}]
    Unless the default is changed, the parameter is automatically resolved
    from the subnet host_routes attribute.
  type: json
TenantIpSubnet:
  default: ''
  description: IP address/subnet on the tenant network
  type: string
TenantNetworkVlanID:
  default: 50
  description: Vlan ID for the tenant network traffic.
  type: number
TenantMtu:
  default: 1500
  description: The maximum transmission unit (MTU) size(in bytes) that is
    guaranteed to pass through the data path of the segments in the
    Tenant network.
  type: number
TenantInterfaceRoutes:
  default: []
  description: >
    Routes for the tenant network traffic.
    JSON route e.g. [{'destination':'10.0.0.0/16', 'nexthop':'10.0.0.1'}]
    Unless the default is changed, the parameter is automatically resolved
    from the subnet host_routes attribute.
  type: json

ExternalMtu:
  default: 1500
  description: The maximum transmission unit (MTU) size(in bytes) that is
    guaranteed to pass through the data path of the segments in the
    External network.
  type: number

DnsServers: # Override this via parameter_defaults
  default: []
  description: >
    DNS servers to use for the Overcloud (2 max for some implementations).
    If not set the nameservers configured in the ctlplane subnet's
    dns_nameservers attribute will be used.
  type: comma_delimited_list
DnsSearchDomains: # Override this via parameter_defaults
  default: []
  description: A list of DNS search domains to be added (in order) to
  resolv.conf.
```

```

    type: comma_delimited_list
#####
resources:
  OsNetConfigImpl:
    type: OS::Heat::SoftwareConfig
    properties:
      group: script
      config:
        str_replace:
          template:
            get_file: ../../scripts/run-os-net-config.sh
        params:
          $network_config:
            network_config:

##### Main Interface [Provision]
  - type: interface
    name: nic1
    mtu:
      get_param: ControlPlaneMtu
    use_dhcp: false
    dns_servers:
      get_param: DnsServers
    domain:
      get_param: DnsSearchDomains
    addresses:
      - ip_netmask:
          list_join:
            - /
            - - get_param: ControlPlaneIp
              - get_param: ControlPlaneSubnetCidr
    routes:
      list_concat_unique:
        - get_param: ControlPlaneStaticRoutes
        - - default: true
          next_hop:
            get_param: ControlPlaneDefaultRoute

##### Main Interface [VLAN]
  - type: ovs_bridge
    name: br-local
    dns_server:
      get_param: DnsServers
    use_dhcp: false

    members:
##### Sub Interface
  - type: interface
    name: nic2
    mtu:
      get_attr: [MinViableMtu, value]

```

```
# force the MAC address of the bridge to this interface
primary: true
##### Sub Interface [Storage]
- type: vlan
  mtu:
    get_param: StorageMtu
  vlan_id:
    get_param: StorageNetworkVlanID
  addresses:
  - ip_netmask:
    get_param: StorageIpSubnet
  routes:
    list_concat_unique:
      - get_param: StorageInterfaceRoutes
##### Sub Interface [StorageMgmt]
- type: vlan
  mtu:
    get_param: StorageMgmtMtu
  vlan_id:
    get_param: StorageMgmtNetworkVlanID
  addresses:
  - ip_netmask:
    get_param: StorageMgmtIpSubnet
  routes:
    list_concat_unique:
      - get_param: StorageMgmtInterfaceRoutes
##### Sub Interface [InternalApi]
- type: vlan
  mtu:
    get_param: InternalApiMtu
  vlan_id:
    get_param: InternalApiNetworkVlanID
  addresses:
  - ip_netmask:
    get_param: InternalApiIpSubnet
  routes:
    list_concat_unique:
      - get_param: InternalApiInterfaceRoutes
##### Sub Interface [Tenant]
- type: vlan
  mtu:
    get_param: TenantMtu
  vlan_id:
    get_param: TenantNetworkVlanID
  addresses:
  - ip_netmask:
    get_param: TenantIpSubnet
  routes:
    list_concat_unique:
      - get_param: TenantInterfaceRoutes
```



```
##### Main Interface [External - NIC]
- type: ovs_bridge
  name: bridge_name
  mtu:
    get_param: ExternalMtu
  dns_servers:
    get_param: DnsServers
  use_dhcp: false
  addresses:
  - ip_netmask:
    get_param: ExternalIpSubnet
  routes:
    list_concat_unique:
      - get_param: ExternalInterfaceRoutes
      - - default: true
        next_hop:
          get_param: ExternalInterfaceDefaultRoute
  members:
  - type: interface
    name: nic3
    mtu:
      get_param: ExternalMtu
    use_dhcp: false
    primary: true
```

#####

```
outputs:
  OS::stack_id:
    description: The OsNetConfigImpl resource.
    value:
      get_resource: OsNetConfigImpl(undercloud)
```

From: <https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link: [https://atl.kr/dokuwiki/doku.php/redhat\\_openstack\\_16.1\\_installation?rev=1644303149](https://atl.kr/dokuwiki/doku.php/redhat_openstack_16.1_installation?rev=1644303149)

Last update: 2022/02/08 06:52

