

RHEL7 iSCSI	3
	3
BackStore	3
iSCSI Target	3

RHEL7 iSCSI

iSCSI Target 가

```
[user@host]# yum install targetcli
[user@host]# systemctl enable target
[user@host]# systemctl start target
```

BackStore

Backstore iSCSI . iscsi target
backstore 4가 가 .

1. FILEIO : FILE
2. BLOCK :
3. PSCSI : SCSI
4. Memory Copy RAM disk (Linux RAMDISK_MCP) :

PSCSI	Pass-through SCSI	SCSI	ALUA
	VMWARE ESXi		
BLOCK			

iSCSI Target

```
[root@storage ~]# targetcli
Warning: Could not load preferences file /root/.targetcli/prefs.bin.
targetcli shell version 2.1.fb41
Copyright 2011-2013 by Datera, Inc and others.
For help on commands, type 'help'.

/> iscsi/
/iscsi> create
Created target iqn.2003-01.org.linux-iscsi.storage.x8664:sn.2c54b81ee88a.
Created TPG 1.
Global pref auto_add_default_portal=true
Created default portal listening on all IPs (0.0.0.0), port 3260.
/iscsi>
```

create IQN IQN .

```
/iscsi> create iqn.2006-04.com.example:444  
Created target iqn.2006-04.com.example:444  
Created TPG1
```

```
ls iqn.2006-04.com.example:444 .
```

```
/iscsi> ls  
o- iscsi .....  
[Targets: 1]  
  o- iqn.2003-01.org.linux-iscsi.storage.x8664:sn.2c54b81ee88a  
  ..... [TPGs: 1]  
    o- tpg1 ..... [no-gen-  
acls, no-auth]  
      o- acls ..... [ACLs: 0]  
      ..... [LUNs: 0]  
        o- luns ..... [LUNs: 0]  
        ..... [LUNs: 0]  
          o- portals .....  
[Portals: 1]  
    o- 0.0.0.0:3260 ..... [OK]  
..... [OK]  
/iscsi>
```

From: <https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link: https://at1.kr/dokuwiki/doku.php/rhel7_iscsi_%EA%B5%AC%EC%84%B1%ED%95%98%EA%B8%B0?rev=1457221025

Last update: 2016/03/05 23:37

