

**RHEL7 Sealing** ..... 3  
..... 4



# RHEL7 Sealing

가

- ( 가 )

```
# yum install initial-setup<----- Customer has to register system for
install this latest package.
```

- ssh host key

```
# rm -rf /etc/ssh/ssh_host_*
```

- /etc/sysconfig/network-scripts/ifcfg-ethx MAC address  
ip address, dns, gateway

```
DEVICE="eth0"
BOOTPROTO="dhcp"
HWADDR="AA:BB:CC:DD:EE:FF" <----- remove this line
NM_CONTROLLED="yes"
ONBOOT="yes"
TYPE="Ethernet"
UUID="954bd22c-f96c-4b59-9445-b39dd86ac8ab" <----- remove this line
```

- udev

```
# rm -rf /etc/udev/rules.d/70-persistent-*
```

- localhost.localdomain

```
# cat /etc/hostname
localhost.localdomain
```

- /etc/machine-id machine-id

```
# cd /etc
# chmod 777 machine-id
# vi machine-id
delete machine id.
# chmod 444 machine-id
```

- ( 가 )

```
~~~  
# systemctl enable initial-setup-graphical.service  
or  
# systemctl enable initial-setup-text.service  
or  
# systemctl enable initial-setup.service  
~~~
```

- 

```
# subscription-manager unregister  
# subscription-manager remove --all  
# subscription-manager clean
```

- 

```
# poweroff
```

- <https://access.redhat.com/solutions/2271601>

From:  
<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:  
[https://atl.kr/dokuwiki/doku.php/rhel7\\_sealing?rev=1518066163](https://atl.kr/dokuwiki/doku.php/rhel7_sealing?rev=1518066163)

Last update: **2018/02/08 05:02**

