

- RHEV 3.6 Backup / Restore** ..... 3
  - ..... 3
  - ..... 3
  - ..... 3
  - RHEVM ..... 3
- script** ..... 5
  - DB Corruption** ..... 6
  - Memory Size** ..... 7



# RHEV 3.6 Backup / Restore

— 2016/04/16 01:10

```

Self-Hosted Engine      Maintenance mode      .
Self Host                Manager VM  maintenance      .

```

```
hosted-engine --set-maintenance --mode=global
```

Manager

```
[root@host]# engine-backup --scope=all --mode=backup --file=BACKUP_FILE --log=LOG_FILE
```

Red Hat Enterprise Virtualization Manager 가  
 Manager 가

1. Red Hat Enterprise Virtualization Manager
2. Red Hat Enterprise Linux
3. Manager 가 Red Hat Enterprise Virtualization Manager
- 4.

## RHEVM

```
RHEVM . Self host maintenance
```

```
[root@host1 ~]# hosted-engine --set-maintenance --mode=global
```

RHEVM

ovirt-engine

.

```
[root@host]# service ovirt-engine stop

[root@host]# engine-cleanup

[ INFO ] Stage: Initializing
[ INFO ] Stage: Environment setup
          Configuration files: ['/etc/ovirt-engine-setup.conf.d/10-
packaging-wsp.conf', '/etc/ovirt-engine-setup.conf.d/10-packaging.conf',
'/etc/ovirt-engine-setup.conf.d/20-setup-ovirt-post.conf']
          Log file: /var/log/ovirt-engine/setup/ovirt-engine-
remove-20170208102356-1jfyw3.log
          Version: otopi-1.3.2 (otopi-1.3.2-1.el6ev)
[ INFO ] Stage: Environment packages setup
[ INFO ] Stage: Programs detection
[ INFO ] Stage: Environment customization
          Do you want to remove all components? (Yes, No) [Yes]:
          --== PRODUCT OPTIONS ==--
          Do you want to remove Engine database content? All data will be
lost (Yes, No) [No]: yes
[ INFO ] Stage: Setup validation
          All the installed ovirt components are about to be removed, data
will be lost (OK, Cancel) [Cancel]: ok
[ INFO ] Stage: Transaction setup
[ INFO ] Stopping engine service
[ INFO ] Stopping ovirt-fence-kdump-listener service
[ INFO ] Stopping websocket-proxy service
[ INFO ] Stage: Misc configuration
[ INFO ] Stage: Package installation
[ INFO ] Stage: Misc configuration
[ INFO ] Backing up PKI configuration and keys
[ INFO ] Backing up database localhost:engine to '/var/lib/ovirt-
engine/backups/engine-20170208102416.PcFb92.dump'.
[ INFO ] Clearing Engine database engine
[ INFO ] Removing files
[ INFO ] Reverting changes to files
[ INFO ] Stage: Transaction commit
[ INFO ] Stage: Closing up
          --== SUMMARY ==--
          A backup of the Engine database is available at /var/lib/ovirt-
engine/backups/engine-20170208102416.PcFb92.dump
          ovirt-engine has been removed
          A backup of PKI configuration and keys is available at
/var/lib/ovirt-engine/backups/engine-pki-2017020810241520jLvC.tar.gz
          Engine setup successfully cleaned up
          --== END OF SUMMARY ==--
[ INFO ] Stage: Clean up
          Log file is located at /var/log/ovirt-engine/setup/ovirt-engine-
remove-20170208102356-1jfyw3.log
```

```
[ INFO ] Generating answer file '/var/lib/ovirt-engine/setup/answers/20170208102423-cleanup.conf'
[ INFO ] Stage: Pre-termination
[ INFO ] Stage: Termination
[ INFO ] Execution of cleanup completed successfully

[root@host]# su - postgres -c psql
alter role engine encrypted password 'PASSWORD';

[root@host]# engine-backup --mode=restore --scope=all --file=BACKUP_FILE --log=LOG_FILE --change-db-credentials --db-host=localhost --db-name=engine --db-user=engine --db-password --restore-permissions

[root@host]# engine-setup
```

## script

```
#!/bin/bash
# Usage : restore.sh DB_PASS RESTORE_FILE
#

if [ $# -ne 2 ]
then
    echo "Usage : restore.sh <DB_PASS> <RESTORE_FILE>";
    exit 1;
fi

PASSWORD=$1
RESTORE_FILE=$2

##### check daemon
echo "check ovirt-engine daemon..."
service ovirt-engine status
if [ $? -ne 3 ]
then
    echo "Service ovirt-engine is not stopped.";
    echo "Service ovirt-engine daemon MUST stop.";
    echo "Exit";
    exit 1;
fi

engine-cleanup << EOF
yes
```

```

ok
ok
EOF

if [ $? -ne 0 ]
then
    echo "engine-cleanup is not completed";
    echo "Exit";
    exit 1;
fi

su - postgres -c psql << EOF
alter role engine encrypted password '$PASSWORD';
\q
EOF

if [ $? -ne 0 ]
then
    echo "db password is not set";
    echo "Exit";
    exit 1;
fi

engine-backup --mode=restore --scope=all --file=$RESTORE_FILE --
log=restore.log --change-db-credentials --db-host=localhost --db-name=engine
--db-user=engine --db-password=$PASSWORD --restore-permissions

engine-setup << EOF
yes
no
ok
EOF

echo "Restore Done"

```

## - DB Corruption

가 engine-cleanup engine-setup 가 database가  
 . psql 가 database list .

```

[root@host2 ~]# su - postgres -c psql
psql (8.4.20)
Type "help" for help.

```

```

postgres=# \l

```

		List of databases		
Ctype	Name	Owner	Encoding	Collation
	Access privileges			

```

-----+-----+-----+-----+-----
-----+-----
engine_20160416011028 | engine_20160416011028 | UTF8      | en_US.UTF-8 |
en_US.UTF-8 |
engine_20160416011808 | engine_20160416011808 | UTF8      | en_US.UTF-8 |
en_US.UTF-8 |
postgres              | postgres              | UTF8      | en_US.UTF-8 |
en_US.UTF-8 |
template0             | postgres              | UTF8      | en_US.UTF-8 |
en_US.UTF-8 | =c/postgres
: postgres=CTc/postgres
template1             | postgres              | UTF8      | en_US.UTF-8 |
en_US.UTF-8 | =c/postgres
: postgres=CTc/postgres
(5 rows)

postgres=# drop database engine_20160416011028;
DROP DATABASE
postgres=# drop database engine_20160416011808;
DROP DATABASE
postgres=# \l

                                List of databases
   Name   | Owner   | Encoding | Collation |  Ctype  | Access
privileges
-----+-----+-----+-----+-----+-----
-----
postgres | postgres | UTF8     | en_US.UTF-8 | en_US.UTF-8 |
template0 | postgres | UTF8     | en_US.UTF-8 | en_US.UTF-8 | =c/postgres
:
postgres=CTc/postgres
template1 | postgres | UTF8     | en_US.UTF-8 | en_US.UTF-8 | =c/postgres
:
postgres=CTc/postgres
(3 rows)

postgres=# \q

```

## - Memory Size

```

가 . 가 가
engine-setup 가 /var/log/messages 가 .

```

```

Apr 21 17:02:53 testvm002 2016-04-21 17:02:53,974 ovirt-engine: ERROR
run:532 Error: Cannot detect JBoss version

```

### engine-setup

```
ENGINE_HEAP_MIN="4096M" #  
ENGINE_HEAP_MAX="4096M"
```

oVirt

8GB	1964M
32GB	7959M
256GB	64565M

From:  
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:  
[https://atl.kr/dokuwiki/doku.php/rhev\\_3.6\\_backup\\_restore?rev=1486549486](https://atl.kr/dokuwiki/doku.php/rhev_3.6_backup_restore?rev=1486549486)

Last update: **2017/02/08 10:24**

