

Last update: rhv_ovirt_ - https://atl.kr/dokuwiki/doku.php/rhv_ovirt_%EB%A1%9C%EA%B7%B8_%EC%88%98%EC%A7%91_%EB%B0%A9%EB%B2%95
2020/06/22 -
08:44 -

RHV / oVirt

RHVM

SPM

: 4.1.8+ 3.6.12+

```
# ovirt-log-collector --hypervisor-per-cluster
```

RHVM

.11 .15

RHV 4

```
# ovirt-log-collector --hosts=*.11,*.15  
or  
# sos-collector --nodes=*.11,*.15
```

RHEV 3.3

```
# engine-log-collector --hosts=*.11,*.15
```

RHEV 3.0/3.1/3.2

```
# rhevm-log-collector collect --hosts=*.11,*.15
```

RHVM

RHV 4

```
# ovirt-log-collector  
or  
# sos-collector
```

RHEV 3.3

```
# engine-log-collector
```

RHEV 3.0/3.1/3.2

```
# rhvm-log-collector collect
```

data-center

1. L
2. .example.com DNS

RHV 4

```
# ovirt-log-collector --cluster=L* --hosts=*.example.com  
or  
# sos-collector -c rhv.cluster=L* --nodes=*.example.com
```

RHEV 3.3

```
# engine-log-collector --cluster=L* --hosts=*.example.com
```

RHEV 3.0/3.1/3.2

```
# rhvm-log-collector collect --cluster=L* --hosts=*.example.com
```

RHV-M ()

RHV 4

```
# ovirt-log-collector --no-hypervisors  
or
```

```
# sos-collector -c rhv.no-hypervisors
```

RHEV 3.3 ~ 3.6

```
# engine-log-collector --no-hypervisors
```

RHEV 3.0/3.1/3.2

```
# rhvm-log-collector collect --no-hypervisors
```

- <https://access.redhat.com/solutions/61546>

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/rhv_ovirt_%EB%A1%9C%EA%B7%B8_%EC%88%98%EC%A7%91_%EB%B0%A9%EB%B2%95

Last update: 2020/06/22 08:44

