

목차

Rocky Linux

.....

3

Rocky Linux Repository

.....

3

Rocky Linux

- CentOS에서 Rocky로 마이그레이션 <https://docs.rockylinux.org/guides/migrate2rocky/>

Rocky Linux Repository

Rocky Linux는 설치를 하게 되면 기본적으로 아래의 3개 레포지토리가 활성화 된다.

- BaseOS
- AppStream
- Extras

레포지토리는 이것 외에도 여러가지가 있다.

```
[root@rocky9-repo yum.repos.d]# dnf repolist all
repo id                                repo name
status
appstream                               Rocky Linux 9 - AppStream
enabled
appstream-debuginfo                    Rocky Linux 9 - AppStream - Debug
disabled
appstream-source                       Rocky Linux 9 - AppStream - Source
disabled
baseos                                  Rocky Linux 9 - BaseOS
enabled
baseos-debuginfo                       Rocky Linux 9 - BaseOS - Debug
disabled
baseos-source                          Rocky Linux 9 - BaseOS - Source
disabled
crb                                     Rocky Linux 9 - CRB
disabled
crb-debuginfo                          Rocky Linux 9 - CRB - Debug
disabled
crb-source                             Rocky Linux 9 - CRB - Source
disabled
devel                                  Rocky Linux 9 - Devel WARNING! FOR
BUILDROOT ONLY DO NOT LEAVE ENABLED disabled
devel-debuginfo                        Rocky Linux 9 - Devel Debug WARNING!
FOR BUILDROOT ONLY DO NOT LEAVE ENABLED disabled
devel-source                           Rocky Linux 9 - Devel Source WARNING!
FOR BUILDROOT ONLY DO NOT LEAVE ENABLED disabled
extras                                 Rocky Linux 9 - Extras
enabled
extras-debuginfo                       Rocky Linux 9 - Extras Debug
disabled
extras-source                          Rocky Linux 9 - Extras Source
disabled
```

highavailability disabled	Rocky Linux 9 - High Availability
highavailability-debuginfo Debug	Rocky Linux 9 - High Availability - disabled
highavailability-source Source	Rocky Linux 9 - High Availability - disabled
nfv disabled	Rocky Linux 9 - NFV
nfv-debuginfo disabled	Rocky Linux 9 - NFV Debug
nfv-source disabled	Rocky Linux 9 - NFV Source
plus disabled	Rocky Linux 9 - Plus
plus-debuginfo disabled	Rocky Linux 9 - Plus - Debug
plus-source disabled	Rocky Linux 9 - Plus - Source
resilientstorage disabled	Rocky Linux 9 - Resilient Storage
resilientstorage-debuginfo Debug	Rocky Linux 9 - Resilient Storage - disabled
resilientstorage-source Source	Rocky Linux 9 - Resilient Storage - disabled
rt disabled	Rocky Linux 9 - Realtime
rt-debuginfo disabled	Rocky Linux 9 - Realtime Debug
rt-source disabled	Rocky Linux 9 - Realtime Source
sap disabled	Rocky Linux 9 - SAP
sap-debuginfo disabled	Rocky Linux 9 - SAP Debug
sap-source disabled	Rocky Linux 9 - SAP Source
saphana disabled	Rocky Linux 9 - SAPHANA
saphana-debuginfo disabled	Rocky Linux 9 - SAPHANA Debug
saphana-source disabled	Rocky Linux 9 - SAPHANA Source

위와 같은 레포지토리 목록을 확인할 수 있으며 Disabled 된 레포지토리는 `dnf config-manager -set-enable <REP0>` 명령어로 활성화 할 수 있다.

```
[root@rocky9-repo]# dnf config-manager --set-enable highavailability plus
[root@rocky9-repo]# dnf repolist all
```

repo id	repo name
---------	-----------

status	
appstream	Rocky Linux 9 - AppStream
enabled	
appstream-debuginfo	Rocky Linux 9 - AppStream - Debug
disabled	
appstream-source	Rocky Linux 9 - AppStream - Source
disabled	
baseos	Rocky Linux 9 - BaseOS
enabled	
baseos-debuginfo	Rocky Linux 9 - BaseOS - Debug
disabled	
baseos-source	Rocky Linux 9 - BaseOS - Source
disabled	
crb	Rocky Linux 9 - CRB
disabled	
crb-debuginfo	Rocky Linux 9 - CRB - Debug
disabled	
crb-source	Rocky Linux 9 - CRB - Source
disabled	
devel	Rocky Linux 9 - Devel WARNING! FOR
BUILDROOT ONLY DO NOT LEAVE ENABLED	disabled
devel-debuginfo	Rocky Linux 9 - Devel Debug WARNING!
FOR BUILDROOT ONLY DO NOT LEAVE ENABLED	disabled
devel-source	Rocky Linux 9 - Devel Source WARNING!
FOR BUILDROOT ONLY DO NOT LEAVE ENABLED	disabled
extras	Rocky Linux 9 - Extras
enabled	
extras-debuginfo	Rocky Linux 9 - Extras Debug
disabled	
extras-source	Rocky Linux 9 - Extras Source
disabled	
highavailability	Rocky Linux 9 - High Availability
enabled	
highavailability-debuginfo	Rocky Linux 9 - High Availability -
Debug	disabled
highavailability-source	Rocky Linux 9 - High Availability -
Source	disabled
nfv	Rocky Linux 9 - NFV
disabled	
nfv-debuginfo	Rocky Linux 9 - NFV Debug
disabled	
nfv-source	Rocky Linux 9 - NFV Source
disabled	
plus	Rocky Linux 9 - Plus
enabled	
plus-debuginfo	Rocky Linux 9 - Plus - Debug
disabled	
plus-source	Rocky Linux 9 - Plus - Source
disabled	
resilientstorage	Rocky Linux 9 - Resilient Storage
disabled	

resilientstorage-debuginfo	Rocky Linux 9 - Resilient Storage - disabled
Debug	
resilientstorage-source	Rocky Linux 9 - Resilient Storage - disabled
Source	
rt	Rocky Linux 9 - Realtime
disabled	
rt-debuginfo	Rocky Linux 9 - Realtime Debug
disabled	
rt-source	Rocky Linux 9 - Realtime Source
disabled	
sap	Rocky Linux 9 - SAP
disabled	
sap-debuginfo	Rocky Linux 9 - SAP Debug
disabled	
sap-source	Rocky Linux 9 - SAP Source
disabled	
saphana	Rocky Linux 9 - SAPHANA
disabled	
saphana-debuginfo	Rocky Linux 9 - SAPHANA Debug
disabled	
saphana-source	Rocky Linux 9 - SAPHANA Source
disabled	

From:

<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:

https://atl.kr/dokuwiki/doku.php/rocky_linux?rev=1729230193

Last update:

2024/10/18 05:43

