

rsyslog send to remote server 3
rsyslog 3
rsyslog 3
Apache **rsyslog** 3
..... 4

rsyslog send to remote server

syslog rsyslog syslog rsyslog syslog

Fedora 10 rsyslog가 Linux OS rsyslog
 . Unix OS syslog .

rsyslog /etc/rsyslog.conf , syslog
 /etc/syslog.conf . 514 UDP, TCP 가

rsyslog

/etc/rsyslog.conf

```
# Provides UDP syslog reception
$ModLoad imudp
$UDPServerRun 514

# Provides TCP syslog reception
$ModLoad imtcp
$InputTCPServerRun 514
```

rsyslog

/etc/rsyslog.conf

```
# UDP
*.info @ IP
*.info @ IP:

# TCP
*.info @@ IP
*.info @@ IP:
```

Apache rsyslog

가 ErrorLog, CustomLog syslog .
 local7 .

```
#  
ErrorLog logs/error_log  
# rsyslog    local0  
ErrorLog syslog:local0
```

가 . /etc/rsyslog.conf

```
local0.* @syslog.example.com  
#  
& ~
```

```
systemctl restart rsyslog  
systemctl restart httpd
```

- <https://access.redhat.com/solutions/20745>
- <https://access.redhat.com/articles/2318351>
- <https://m.blog.naver.com/scvpark/221017723884>

From:
<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:
https://atl.kr/dokuwiki/doku.php/rsyslog_send_to_remote_server

Last update: **2020/12/15 02:03**

