

Scouter Java agent 3

Scouter Java agent

```
2018-05-25 13:31:13,891 ERROR [io.undertow.request] (default task-1)
UT005023: Exception handling request to /paper/:
java.lang.NoClassDefFoundError: scouter/agent/trace/TraceMain
    at javax.servlet.http.HttpServlet.service(HttpServlet.java)
    at
io.undertow.servlet.handlers.ServletHandler.handleRequest(ServletHandler.java:85)
    at
io.undertow.servlet.handlers.security.ServletSecurityRoleHandler.handleRequest(ServletSecurityRoleHandler.java:62)
    at
io.undertow.servlet.handlers.ServletDispatchingHandler.handleRequest(ServletDispatchingHandler.java:36)
    at
org.wildfly.extension.undertow.security.SecurityContextAssociationHandler.handleRequest(SecurityContextAssociationHandler.java:78)
    at
io.undertow.server.handlers.PredicateHandler.handleRequest(PredicateHandler.java:43)
    at
io.undertow.servlet.handlers.security.SSLInformationAssociationHandler.handleRequest(SSLInformationAssociationHandler.java:131)
    at
io.undertow.servlet.handlers.security.ServletAuthenticationCallHandler.handleRequest(ServletAuthenticationCallHandler.java:57)
    at
io.undertow.server.handlers.PredicateHandler.handleRequest(PredicateHandler.java:43)
    at
io.undertow.security.handlers.AbstractConfidentialityHandler.handleRequest(AbstractConfidentialityHandler.java:46)
    at
io.undertow.servlet.handlers.security.ServletConfidentialityConstraintHandler.handleRequest(ServletConfidentialityConstraintHandler.java:64)
    at
io.undertow.security.handlers.AuthenticationMechanismsHandler.handleRequest(AuthenticationMechanismsHandler.java:60)
    at
io.undertow.servlet.handlers.security.CachedAuthenticatedSessionHandler.handleRequest(CachedAuthenticatedSessionHandler.java:77)
    at
io.undertow.security.handlers.NotificationReceiverHandler.handleRequest(NotificationReceiverHandler.java:50)
    at
io.undertow.security.handlers.AbstractSecurityContextAssociationHandler.handleRequest(AbstractSecurityContextAssociationHandler.java:43)
    at
```

```
io.undertow.server.handlers.PredicateHandler.handleRequest(PredicateHandler.java:43)
    at
org.wildfly.extension.undertow.security.jacc.JACCContextIdHandler.handleRequest(JACCContextIdHandler.java:61)
    at
io.undertow.server.handlers.PredicateHandler.handleRequest(PredicateHandler.java:43)
    at
org.wildfly.extension.undertow.deployment.GlobalRequestControllerHandler.handleRequest(GlobalRequestControllerHandler.java:68)
    at
io.undertow.server.handlers.PredicateHandler.handleRequest(PredicateHandler.java:43)
    at
io.undertow.servlet.handlers.ServletInitialHandler.handleFirstRequest(ServletInitialHandler.java:292)
    at
io.undertow.servlet.handlers.ServletInitialHandler.access$100(ServletInitialHandler.java:81)
    at
io.undertow.servlet.handlers.ServletInitialHandler$2.call(ServletInitialHandler.java:138)
    at
io.undertow.servlet.handlers.ServletInitialHandler$2.call(ServletInitialHandler.java:135)
    at
io.undertow.servlet.core.ServletRequestContextThreadSetupAction$1.call(ServletRequestContextThreadSetupAction.java:48)
    at
io.undertow.servlet.core.ContextClassLoaderSetupAction$1.call(ContextClassLoaderSetupAction.java:43)
    at
org.wildfly.extension.undertow.security.SecurityContextThreadSetupAction.lambda$create$0(SecurityContextThreadSetupAction.java:105)
    at
org.wildfly.extension.undertow.deployment.UndertowDeploymentInfoService$UndertowThreadSetupAction.lambda$create$0(UndertowDeploymentInfoService.java:1508)
    at
org.wildfly.extension.undertow.deployment.UndertowDeploymentInfoService$UndertowThreadSetupAction.lambda$create$0(UndertowDeploymentInfoService.java:1508)
    at
org.wildfly.extension.undertow.deployment.UndertowDeploymentInfoService$UndertowThreadSetupAction.lambda$create$0(UndertowDeploymentInfoService.java:1508)
    at
org.wildfly.extension.undertow.deployment.UndertowDeploymentInfoService$UndertowThreadSetupAction.lambda$create$0(UndertowDeploymentInfoService.java:1508)
```

```

8)
    at
io.undertow.servlet.handlers.ServletInitialHandler.dispatchRequest(ServletIn
itialHandler.java:272)
    at
io.undertow.servlet.handlers.ServletInitialHandler.access$000(ServletInitial
Handler.java:81)
    at
io.undertow.servlet.handlers.ServletInitialHandler$1.handleRequest(ServletIn
itialHandler.java:104)
    at
io.undertow.server.Connectors.executeRootHandler(Connectors.java:326)
    at
io.undertow.server.HttpServerExchange$1.run(HttpServerExchange.java:812)
    at
java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:11
49)
    at
java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:6
24)
        at java.lang.Thread.run(Thread.java:748)
Caused by: java.lang.ClassNotFoundException: scouter.agent.trace.TraceMain
from [Module "javax.servlet.api" from local module loader @3cb5cdba (finder:
local module finder @56cbfb61 (roots:
/app/jboss/modules,/app/jboss/modules/system/layers/base))]
    at
org.jboss.modules.ModuleClassLoader.findClass(ModuleClassLoader.java:198)
    at
org.jboss.modules.ConcurrentClassLoader.performLoadClassUnchecked(Concurrent
ClassLoader.java:412)
    at
org.jboss.modules.ConcurrentClassLoader.performLoadClass(ConcurrentClassLoad
er.java:400)
    at
org.jboss.modules.ConcurrentClassLoader.loadClass(ConcurrentClassLoader.java
:116)
    ... 39 more

```

```

scouter java agent          javagent  scouter.conf
    system.pkgs  scouter
JAVA_OPTS -Djboss.modules.system.pkgs=scouter  가

```

```

### scouter agent
JAVA_OPTS="$JAVA_OPTS -
javaagent:/app/scouter/scouter/agent.java/scouter.agent.jar"
JAVA_OPTS="$JAVA_OPTS -
Dscouter.config=/app/scouter/scouter/agent.java/conf/test11.conf"

### byteman

```

```
JAVA_OPTS="$JAVA_OPTS -Djboss.modules.system.pkgs=org.jboss.byteman,scouter"
```

From: <https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link: https://atl.kr/dokuwiki/doku.php/scouter_java_agent_%EC%84%A4%EC%A0%95%EC%8B%9C_%EC%A3%BC%EC%9D%98%ED%95%A0%EC%A0%90?rev=1527224556

Last update: 2018/05/25 05:02

