

**selinux - SSH port** ..... 3  
    가 ..... 3  
        ..... 4



# selinux - SSH port

```
SSHD . 22002 .
```

```
vi /etc/ssh/sshd_config
```

```
<<----Output Redacted----->>
# If you want to change the port on a SELinux system, you have to tell
# SELinux about this change.
# semanage port -a -t ssh_port_t -p tcp #PORTNUMBER
#
Port 22002
#AddressFamily any
#ListenAddress 0.0.0.0
#ListenAddress ::
<<l----Ourput Redacted----->>
```

```
selinux          ssh_port_t .
```

```
$ semanage port -a -t ssh_port_t -p tcp 22002
```

```
$ semanage port -l | grep ssh
```

```
sshd.service .
```

```
$ systemctl restart sshd.service
```

## 가

firewall

```
$ firewall-cmd --permanent --add-port=22002/tcp
$ firewall-cmd --reload
```

iptables

```
$ iptables -I INPUT 4 -p tcp -m multiport --destination-ports 22002 -m state
--state NEW -j ACCEPT

$ iptables -I INPUT 4 -p tcp -m multiport --dport 22002 -j ACCEPT
$ service iptables save
```

- <https://access.redhat.com/solutions/3955191>

From:  
<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:  
[https://atl.kr/dokuwiki/doku.php/selinux\\_-\\_ssh\\_port\\_%EB%B3%80%EA%B2%BD](https://atl.kr/dokuwiki/doku.php/selinux_-_ssh_port_%EB%B3%80%EA%B2%BD)

Last update: **2022/09/23 02:21**

