

**selinux - SSH port** ..... 3  
..... 3



# selinux - SSH port

```
SSHD . 2200 .
```

```
vi /etc/ssh/sshd_config
```

```
<<----Output Redacted----->>
# If you want to change the port on a SELinux system, you have to tell
# SELinux about this change.
# semanage port -a -t ssh_port_t -p tcp #PORTNUMBER
#
Port 2200
#AddressFamily any
#ListenAddress 0.0.0.0
#ListenAddress ::
<<l-----Ourput Redacted----->>
```

```
selinux          ssh_port_t .
```

```
$ semanage port -a -t ssh_port_t -p tcp 2200
```

```
$ semanage port -l | grep ssh
```

```
sshd.service .
```

```
$ systemctl restart sshd.service
```

- <https://access.redhat.com/solutions/3955191>

From:  
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:  
[https://atl.kr/dokuwiki/doku.php/selinux\\_-\\_ssh\\_port\\_%EB%B3%80%EA%B2%BD?rev=1645174377](https://atl.kr/dokuwiki/doku.php/selinux_-_ssh_port_%EB%B3%80%EA%B2%BD?rev=1645174377)

Last update: 2022/02/18 08:52

