

Session Cookie name 3

EAP 7.x 3

 Application level 3

 Server level 3

mod-jk 4

 4

Session Cookie name

EAP 7.x

Application level

Servlet 3.0 web.xml <cookie-config>

```
<web-app xmlns="http://java.sun.com/xml/ns/javaee"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/javaee
http://java.sun.com/xml/ns/javaee/web-app_3_0.xsd"
  version="3.0">
  ... (snip) ...

  <session-config>
    <cookie-config>
      <name>MYSESSIONID</name>
      ... (snip) ...
    </cookie-config>
  </session-config>

  ... (snip) ...
</web-app>
```

Server level

undertow 가 .

```
<subsystem xmlns="urn:jboss:domain:undertow:3.1">
  ...
  <servlet-container name="default">
    <jsp-config/>
    <session-cookie name="DESIREDCOOKIEHERE"/> <!-- added -->
    <websockets/>
  </servlet-container>
```

CLI

```
# standalone
```

```

/subsystem=undertow/servlet-container=default/setting=session-
cookie:add(name=DESIREDCOOKIEHERE)
# domain
/profile=filename/subsystem=undertow/servlet-
container=default/setting=session-cookie:add(name=DESIREDCOOKIEHERE)

```

mod-jk

session cookie name	mod-jk	WEB-WAS	Sticky
Session	.	sticky session	session cookie
jvmRoute	sticky	JSESSIONID	가
worker	balancer	session_cookie	session
cookie name	.	WAS	

```
worker.balancer.session_cookie=JSESSIONID_CUSTOM
```

- <https://access.redhat.com/solutions/17910>

From:
<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:
https://atl.kr/dokuwiki/doku.php/session_cookie_name_%EB%B3%80%EA%B2%BD

Last update: **2022/03/11 09:19**

