

- Session Timeout** 3
- JBoss EAP 4.x 5.x*** 3
 - JBoss EAP 6 3
 - JBoss EAP 7 4

Session Timeout

: <https://access.redhat.com/solutions/31400>

JBoss EAP 4.x 5.x

1. The session timeout hierarchy in JBoss EAP is (from lowest to highest precedence):

- org.apache.catalina.session.Manager.maxInactiveInterval (default 60 seconds)
- Set globally in JBossWeb's web.xml (default 30 minutes):

For EAP 4.x, \$JBOSS_HOME/server/\$PROFILE/deploy/jboss-web.deployer/conf/web.xml For EAP 5.x, \$JBOSS_HOME/server/\$PROFILE/deployers/jbossweb.deployer/web.xml

- Set in the web application's web.xml: WEB-INF/web.xml
- Dynamically set in code by javax.servlet.http.HttpSession#setMaxInactiveInterval(int)

1. In other words, if the session timeout is set programmatically in the web application via javax.servlet.http.HttpSession#setMaxInactiveInterval(int). This takes precedence over the timeout set in the webapps web.xml, which takes precedence over configured timeout in JBossWeb's global web.xml.

1. In web.xml, the configuration format is:

```
<session-config>
  <session-timeout>30</session-timeout>
</session-config>
```

JBoss EAP 6

For EAP 6 up to 6.3 it is not possible to set session timeout globally because there is no global web.xml and there is no setting in the web subsystem currently. The default Http session timeout in EAP 6 is 30 minutes and it is hard-coded at the container level. If there is a need to set the session timeout, this should be done in the web application's web.xml.

Starting from EAP 6.4 you can modify the default session timeout by changing the default-session-timeout attribute of the web subsystem. Setting it 15 minutes for example:

```
/subsystem=web:write-attribute(name=default-session-timeout,value=15)
```

result in xml:

```
<subsystem xmlns="urn:jboss:domain:web:2.2" default-virtual-
server="default-host" native="false" default-session-timeout="15">
  ...
```

</subsystem>

JBoss EAP 7

HTTP , HTTP HTTP JBoss EAP .
 가 HTTP
 HTTP HTTP 가
 가
 HTTP web.xml JBoss EAP HTTP
 web.xml
 undertow servlet-container default-session-
 timeout . default-session-timeout
 30 .

```

/subsystem=undertow/servlet-container=default:write-attribute(name=default-
session-timeout, value=60)
# JBoss reload
reload

```

configuration .

<WRAP prewrap>

```

<subsystem xmlns="urn:jboss:domain:undertow:3.1">
  <buffer-cache name="default"/>
  <server name="default-server">
    <ajp-listener name="ajp" socket-binding="ajp"/>
    <http-listener name="default" socket-binding="http"
redirect-socket="https"/>
    <host name="default-host" alias="localhost">
      <location name="/" handler="welcome-content"/>
      <filter-ref name="server-header"/>
      <filter-ref name="x-powered-by-header"/>
    </host>
  </server>
<!-- ## . ## -->
  <servlet-container name="default" default-session-timeout="60">
    <jsp-config/>
    <websockets/>
  </servlet-container>
  <handlers>
    <file name="welcome-content"
path="${jboss.home.dir}/welcome-content"/>

```

```
    </handlers>
    <filters>
      <response-header name="server-header" header-name="Server"
header-value="JBoss-EAP/7"/>
      <response-header name="x-powered-by-header" header-name="X-
Powered-By" header-value="Undertow/1"/>
    </filters>
  </subsystem>
```

</WRAP

From:
<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:
https://atl.kr/dokuwiki/doku.php/session_timeout_%EC%84%A4%EC%A0%95%ED%95%98%EA%B8%B0?rev=1495526601

Last update: **2017/05/23 08:03**

