

- SetUID, SetGID, Sticky Bit** 3
- * 3
- 1. 3
- * **가** 3
- * **SetUID, SetGID, Sticky Bit** ? 4

SetUID, SetGID, Sticky Bit

: <http://soul0.tistory.com/246>

SetUID, SetGID, Sticky Bit ? ?

*

SetUID SetGID, Sticky Bit . Other , AIX,
 LINUX /tmp 가 Other rwX
 . Other , WebSphere
 /tmp/javasharedresources .. WAS .

1.

- - Instance, NodeAgnent, DMGR
 - JVM Option -Xshareclasses:node
 가 ()

* 가

1. /tmp/javasharedresources check ,
 javasharedresources permission ..

2. -Xshareclasses 가 :
 controlDir=<your_was_home>/tmp 777 . 1

3. disable .(none)

WAS 가 OS /tmp /tmp/.com_ibm_tools_attach/
 /tmp/javasharedresources/ /tmp/javasharedresources java class cache
 , cache Version 6.1
 , (default). shared resource ,
 javasharedresources 가 777 . WAS umask
 022 .. directory 644 .
 shared resource , shared 가 가 ,
 가 . 가 risk 가 (?) ? (
 .. /tmp ..
)

* SetUID, SetGID, Sticky Bit ?

(w), (x)가 . , , , , (A) 가
(B) A SetUID, SetGID, Sticky Bit가 가
(SetUID SetGID).

1. SetUID

. SetUID가

SetUID 4xxx . (100 . xxx 가 s가 . ex) chmod 4750 httpd
SetUID (rwsr-x—)

2. SetGID

. SetGID가

SetGID 2xxx . (010 . xxx 가 s가 . ex) chmod 2750 httpd (rwxr-s—)

3. Sticky Bit Sticky Bit가 가

root .

Sticky Bit 1xxx . (001 . xxx 가 t가 . , ,)
Sticky Bit

1. 777 (drwxrwxrwx)

```
. root 가 600 (-rw-----) , 777 (drwxrwxrwx)
```

1-1. 700 (drwx---

1. 가 .

```
root 가 600 (-rw-----) , 700 (drwx-----)
```

2. 1777 (drwxrwxrwt) ← (/tmp) (Sticky Bit)

```
. root 777 (-rwxrwxrwx) , 1777 (drwxrwxrwt)  
. root owner
```

From:

<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:

https://atl.kr/dokuwiki/doku.php/setuid_setgid_sticky_bit?rev=1542555992

Last update: **2018/11/18 15:46**

