

<b>Systemd journal log</b>	.....	3
	.....	3
	.....	4
	.....	5



# Systemd journal log

```
$ journalctl
```

- n 10

```
$ journalctl -n
```

-n 7

```
$ journalctl -n 7
```

## message catalog

-x 가 message catalog 가

```
$ journalctl -xn
```

-n . -e(pager end) pager

```
$ journalctl -x -e
```

가

가

pager 가

가

--no-pager

pager

```
$ journalctl -xn --no-pager | less
```

tail -f

-f

```
$ journalctl -f
```

## PID

\_PID={PID}

가 10

PID

pid 가 872

```
$ journalctl -n _PID=872
```

-p

(emerg, alert, crit, err, warning, notice, info, debug)

가

crit

가

(emerg = 0, debug = 7)

emerg, alert

```
$ journalctl -p critical
```

/

--since --until

20 1 9

```
$ journalctl --since 2020-01-09
```

1 9 , 10 01-11 10 --until . 가 util ~

```
$ journalctl --since 2020-01-09 --until 2020-01-11
```

yesterday, today, tomorrow

```
$ journalctl --since yesterday --until tomorrow
```

10

2

```
$ journalctl --since "-2hour" --until "10min"
```

- <https://www.lesstif.com/system-admin/linux-journalctl-82215080.html>

From:  
<https://atl.kr/dokuwiki/> - AllThatLinux!



Permanent link:

[https://atl.kr/dokuwiki/doku.php/systemd\\_journal\\_log\\_%ED%99%9C%EC%9A%A9](https://atl.kr/dokuwiki/doku.php/systemd_journal_log_%ED%99%9C%EC%9A%A9)

Last update: **2023/03/21 01:32**