

- THP(Transparent Huge Pages)** 3
- THP(Transparent Huge Pages)*** ? 3
- THP*** 3
- THP (in RHEL7)*** 5

THP(Transparent Huge Pages)

: http://www.cubrid.com/zbxe/bbs_developer_faq/3550332

THP(Transparent Huge Pages) ?

THP

CPU Virtual address MMU가 Physical address
 Virtual address Physical address
 Page table TTB (Translation Table Base Address)

CPU가 TTB 가 가 Virtual
 address Physical address 가 Entry 가 가 TLB
 Physical address 가
 (Translation Lookaside Buffer)

CPU가 Virtual Address TLB Virtual Address Entry
 가 (hit) 가
 (miss) TTB(Translation Table Base Address) 1 Physical address
 Physical address 가

hit ratio가 miss 2 가 가
 . (, hit ratio가 TLB 가 .)

hit ratio가 TLB Entry ,
 page page table 가 TLB Entry가 . Entry
 page THP

THP 4KB 2MB 1GB
 RHEL 6

THP 가 disable

THP

```
[root@host]# cat /sys/kernel/mm/transparent_hugepage/enabled
```

```
[always] madvise never -> [always] 가 THP가
always madvise [never] -> [never] 가 THP가
```

•

```
[root@host]# cat /proc/meminfo
```

가 .

```
MemTotal:      1003184 kB
MemFree:       604844 kB
MemAvailable:  750616 kB
Buffers:       884 kB
Cached:        143904 kB
SwapCached:    0 kB
Active:        160624 kB
Inactive:      112368 kB
Active(anon):  128912 kB
Inactive(anon): 6356 kB
Active(file):  31712 kB
Inactive(file): 106012 kB
Unevictable:   0 kB
Mlocked:       0 kB
SwapTotal:     2097148 kB
SwapFree:      2097148 kB
Dirty:         92 kB
Writeback:     0 kB
AnonPages:    128300 kB
Mapped:        37492 kB
Shmem:         7064 kB
Slab:          60876 kB
SReclaimable: 23024 kB
SUnreclaim:   37852 kB
KernelStack:  8480 kB
PageTables:    6220 kB
NFS_Unstable:  0 kB
Bounce:        0 kB
WritebackTmp:  0 kB
CommitLimit:  2598740 kB
Committed_AS: 494544 kB
VmallocTotal: 34359738367 kB
VmallocUsed:   185924 kB
VmallocChunk: 34359535100 kB
HardwareCorrupted: 0 kB
```

```

AnonHugePages:      0 kB
HugePages_Total:    0
HugePages_Free:     0
HugePages_Rsvd:     0
HugePages_Surp:     0
Hugepagesize:       2048 kB
DirectMap4k:        61312 kB
DirectMap2M:        987136 kB
DirectMap1G:        0 kB

```

0 THP가

```

AnonHugePages:      0 kB
HugePages_Total:    0
HugePages_Free:     0
HugePages_Rsvd:     0
HugePages_Surp:     0

```

```

Linux
가 AnonHugePages
가 0
THP
THP disable
[never]
AnonHugePages
가

```

THP (in RHEL7)

RHEL 7 THP

THP tuned

2가

가

Step 1: Initially, we should create a customized version of the currently running profile. The customized version will disable THP. Find out which profile is active, create a copy. In the following example we currently use the throughput-performance profile:

- tuned profile active
- active tuned profile

```
[root@host]# tuned-adm active
```

```

OS가 가 virtual-guest,
throughput-performance

```

```
Current active profile: throughput-performance // in Server default configuration
```

```
Current active profile: virtual-guest // in Virtual OS
```



```
[root@host]# cat /proc/cmdline
BOOT_IMAGE=/vmlinuz-3.10.0-229.20.1.el7.x86_64 root=/dev/mapper/centos-root
ro rd.lvm.lv=centos/root rd.lvm.lv=centos/swap crashkernel=auto rhgb
quiettransparent_hugepage=never
```

From:
<https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://at1.kr/dokuwiki/doku.php/thp_transparent_huge_pages_%E8%B0%EB%8A%A5%EA%B3%BC_%EC%84%A4%EC%A0%95_%EB%B0%A9%EB%B2%95?rev=1458526086

Last update: 2016/03/21 02:08

