

Tomcat

..... 3

Tomcat

```
[user@host]# catalina.sh stop
Using CATALINA_BASE:   /software/tomcat/servers/test
Using CATALINA_HOME:   /software/tomcat
Using CATALINA_TMPDIR: /software/tomcat/servers/test/temp
Using JRE_HOME:        /usr
Using CLASSPATH:       /software/tomcat/bin/bootstrap.jar
Using CATALINA_PID:    /software/tomcat/servers/test/catalina.pid
Tomcat did not stop in time. PID file was not removed.
```

가 가 가 .
가 .

3~40

```
INFO: JK: ajp13 listening on /0.0.0.0:8109 Feb 17, 2016 3:34:43 PM org.apache.jk.server.JkMain
start INFO: Jk running ID=0 time=0/14 config=null Feb 17, 2016 3:34:43 PM
org.apache.catalina.startup.Catalina start INFO: Server startup in 425 ms Feb 17, 2016 3:35:47
PM org.apache.coyote.http11.Http11Protocol pause INFO: Pausing Coyote HTTP/1.1 on
http-0.0.0.0-8180 Feb 17, 2016 3:36:07 PM org.apache.catalina.connector.Connector pause
SEVERE: Protocol handler pause failed java.net.UnknownHostException: centos: centos
```

```
at java.net.InetAddress.getLocalHost(InetAddress.java:1496)
at
org.apache.jk.common.ChannelSocket.unlockSocket(ChannelSocket.java:507)
at org.apache.jk.common.ChannelSocket.pause(ChannelSocket.java:288)
at org.apache.jk.server.JkMain.pause(JkMain.java:739)
at org.apache.jk.server.JkCoyoteHandler.pause(JkCoyoteHandler.java:186)
at org.apache.catalina.connector.Connector.pause(Connector.java:1156)
at
org.apache.catalina.core.StandardService.stop(StandardService.java:578)
at org.apache.catalina.core.StandardServer.stop(StandardServer.java:793)
at org.apache.catalina.startup.Catalina.stop(Catalina.java:662)
at org.apache.catalina.startup.Catalina.start(Catalina.java:629)
at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
at
sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:57)
at
sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
at java.lang.reflect.Method.invoke(Method.java:606)
at org.apache.catalina.startup.Bootstrap.start(Bootstrap.java:289)
at org.apache.catalina.startup.Bootstrap.main(Bootstrap.java:414)
```

hostname resolv

/etc/hosts

127.0.0.1 localhost localhost.localdomain localhost4
localhost4.localdomain4
::1 localhost localhost.localdomain localhost6
localhost6.localdomain6
192.168.240.137 centos

