

tomcat systemd 3

tomcat systemd

/usr/lib/systemd/system

tomcat@.service

- `systemctl start tomcat@instance.service`
- `instance`

```
[Unit]
Description=Tomcat - instance %i
After=syslog.target network.target

[Service]
Type=forking

WorkingDirectory=/app/tomcat/SERVERS/%i
#Environment="JAVA_HOME=/usr/lib/jvm/java-1.8.0-
openjdk-1.8.0.262.b10-0.el7_8.x86_64/"
#Environment="CATALINA_HOME=/usr/local/server/apache-tomcat"
#Environment="CATALINA_BASE=/usr/local/server/apache-tomcat"
#Environment="CATALINA_OPTS=-Xms512M -Xmx1024M -server -XX:+UseParallelGC"
#Environment="JAVA_OPTS=-Djava.security.egd=file:///dev/urandom"

ExecStart=/bin/sh /app/tomcat/SERVERS/%i/bin/tomcat.sh start
ExecStop=/bin/sh /app/tomcat/SERVERS/%i/bin/tomcat.sh stop

User=root
Group=root
UMask=0022
RestartSec=10
#Restart=always

[Install]
WantedBy=multi-user.target
```

systemd

```
[root@host ~]# systemctl daemon-reload
[root@host ~]# systemctl enable tomcat@node11.service
```

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/tomcat_systemd_%EB%93%B1%EB%A1%9D?rev=1607414325

Last update: **2020/12/08 07:58**

