

<b>WAS</b>	.....	3
	.....	3
	.....	3
	.....	3
	.....	5

was\_  
Last update: 2018/06/04 06:32  
– https://atl.kr/dokuwiki/doku.php/was\_%EB%B3%B4%EC%95%88\_%EC%B7%A8%EC%95%BD%EC%A0%90\_%EC%A0%90%EA%B2%80?rev=1528093970

---

# WAS

## Tomcat

server.xml      connector      xpoweredBy, server      가 .

```
<Connector port="8080" protocol="HTTP/1.1"
           connectionTimeout="20000"
           redirectPort="8443"
           xpoweredBy="foo"
           server="bar"
           />
```

## JBoss EAP 6.x

- SERVER

SERVER      . .  
org.apache.coyote.http11.Http11Protocol.SERVER Property      가 .

```
org.apache.coyote.http11.Http11Protocol.SERVER="foo"
```

```
<system-properties>
    <property name="org.apache.coyote.http11.Http11Protocol.SERVER"
value="foo"/>
</system-properties>
```

- X-PoweredBy

X-PoweredBy      JBoss

```
Last update: 2018/06/04 06:32
was_
- https://atl.kr/dokuwiki/doku.php/was_%EB%B3%B4%EC%95%88_%EC%B7%A8%EC%95%BD%EC%A0%90_%EC%A0%90%EA%B2%80?rev=1528093970
```

```
/subsystem=web/configuration=jsp-configuration/:write-attribute(name=x-powered-by,value=false)
{
    "outcome" => "success",
    "response-headers" => {
        "operation-requires-reload" => true,
        "process-state" => "reload-required"
    }
}
```

가 .

```
<subsystem xmlns="urn:jboss:domain:web:1.1" default-virtual-server="default-host" native="false">
    <configuration>
        <jsp-configuration x-powered-by="false"/>
    </configuration>
    ...
    ...
</subsystem>
```

## JBoss EAP 7.x

- Server: JBoss-EAP/7 X-Powered-By: Undertow/1

CLI

```
/subsystem=undertow/server=default-server/host=default-host/filter-ref=x-powered-by-header:remove
/subsystem=undertow/server=default-server/host=default-host/filter-ref=server-header:remove
```

CLI

```
/subsystem=undertow/configuration=filter/response-header=server-header:write-attribute(name=header-value,value=foo)
/subsystem=undertow/configuration=filter/response-header=x-powered-by-header:write-attribute(name=header-value,value=bar)
```

- X-Powered-By: JSP/2.3

## CLI

```
/subsystem=undertow/servlet-container=default/setting=jsp:write-attribute(name=x-powered-by,value=false)
```

- <https://access.redhat.com/solutions/21075>
- <https://tomcat.apache.org/tomcat-8.0-doc/security-howto.html#Connectors>

From:  
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:  
[https://atl.kr/dokuwiki/doku.php/was\\_%EB%B3%B4%EC%95%88\\_%EC%B7%A8%EC%95%BD%EC%A0%90\\_%EC%A0%90%EA%B2%80?rev=1528093970](https://atl.kr/dokuwiki/doku.php/was_%EB%B3%B4%EC%95%88_%EC%B7%A8%EC%95%BD%EC%A0%90_%EC%A0%90%EA%B2%80?rev=1528093970)

Last update: 2018/06/04 06:32

