

WAS 3
 3
 3
 3
 5
Directory Listing 5

was_
Last update: 2019/11/14 04:04 - https://atl.kr/dokuwiki/doku.php/was_%EB%B3%B4%EC%95%88_%EC%B7%A8%EC%95%BD%EC%A0%90_%EC%A0%90%EA%B2%80?rev=1573704270


WAS

Tomcat

server.xml connector server 가 . xpoweredBy="false" 가
 . false가 가 .

```
<Connector port="8080" protocol="HTTP/1.1"
  connectionTimeout="20000"
  redirectPort="8443"
  server="bar"
  xpoweredBy="false"
  />
```

가 X-Powered-By 가 web.xml

 tomcat 6 가 .

```
<init-param>
  <param-name>xpoweredBy</param-name>
  <param-value>>false</param-value>
</init-param>
```

JBoss EAP 6.x

- SERVER

SERVER . 가 .
 org.apache.coyote.http11.Http11Protocol.SERVER Property .

```
org.apache.coyote.http11.Http11Protocol.SERVER="foo"
```

```
<system-properties>
  <property name="org.apache.coyote.http11.Http11Protocol.SERVER"
value="foo"/>
</system-properties>
```

- X-PoweredBy

X-PoweredBy JBoss

```
/subsystem=web/configuration=jsp-configuration/:write-attribute(name=x-
powered-by,value=false)
{
  "outcome" => "success",
  "response-headers" => {
    "operation-requires-reload" => true,
    "process-state" => "reload-required"
  }
}
```

가

```
<subsystem xmlns="urn:jboss:domain:web:1.1" default-virtual-server="default-
host" native="false">
  <configuration>
    <jsp-configuration x-powered-by="false"/>
  </configuration>
  ...
  ...
</subsystem>
```

JBoss EAP 7.x

- Server: JBoss-EAP/7 X-Powered-By: Undertow/1

CLI

```

/subsystem=undertow/server=default-server/host=default-host/filter-ref=x-
powered-by-header:remove
/subsystem=undertow/server=default-server/host=default-host/filter-
ref=server-header:remove

```

CLI

```

/subsystem=undertow/configuration=filter/response-header=server-
header:write-attribute(name=header-value,value=foo)
/subsystem=undertow/configuration=filter/response-header=x-powered-by-
header:write-attribute(name=header-value,value=bar)

```

- X-Powered-By: JSP/2.3

CLI

```

/subsystem=undertow/servlet-container=default/setting=jsp:write-
attribute(name=x-powered-by,value=false)

```

- <https://access.redhat.com/solutions/21075>
- <https://tomcat.apache.org/tomcat-8.0-doc/security-howto.html#Connectors>
- <https://access.redhat.com/solutions/2740891>

Directory Listing

Tomcat

- <https://tomcat.apache.org/tomcat-9.0-doc/default-servlet.html>

Tomcat 9					web.xml
	listings	false			

```

<servlet>
  <servlet-name>default</servlet-name>
  <servlet-class>
    org.apache.catalina.servlets.DefaultServlet
  </servlet-class>
  <init-param>
    <param-name>debug</param-name>

```

was_
Last update: 2019/11/14 04:04 - https://atl.kr/dokuwiki/doku.php/was_%EB%B3%B4%EC%95%88_%EC%B7%A8%EC%95%BD%EC%A0%90_%EC%A0%90%EA%B2%80?rev=1573704270

```
<param-value>0</param-value>
</init-param>
<init-param>
  <param-name>listings</param-name>
  <param-value>>false</param-value>
</init-param>
<load-on-startup>1</load-on-startup>
</servlet>
```

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/was_%EB%B3%B4%EC%95%88_%EC%B7%A8%EC%95%BD%EC%A0%90_%EC%A0%90%EA%B2%80?rev=1573704270

Last update: 2019/11/14 04:04

