

- Zabbix install on Debian 11** 3
- date.timezone* 3
- MySQL* / 4
- Zabbix Server* 4
- Zabbix Agent* 5
- 5

Zabbix install on Debian 11

- <https://wiki.debian.org/Zabbix>

```
root@mon:~# apt install zabbix-server-mysql zabbix-frontend-php php7.4-mysql
php7.4-zip php7.4-xml php7.4-xmlrpc php7.4-sqlite3 php7.4-pspell
php7.4-readline php7.4-mbstring php7.4-json php7.4-gd php7.4-curl php7.4-
bcmath
```

```
root@mon:~# a2enconf zabbix-frontend-php
Enabling conf zabbix-frontend-php.
To activate the new configuration, you need to run:
  systemctl reload apache2
root@mon:~# systemctl restart apache2
```

<http://server/zabbix/> URL 가 .

date.timezone

2가 가 . apache .

php.ini date.timezone 가 .

```
root@mon:~# vim /etc/php/7.4/apache2/php.ini

[Date]
; Defines the default timezone used by the date functions
; http://php.net/date.timezone
date.timezone = Asia/Seoul
```

zabbix php_value .

/etc/apache2/conf-available/zabbix-frontend-php.conf php_value
date.timezone Asia/Seoul 가 .

```
<IfModule mod_php5.c>
  php_value max_execution_time 300
  php_value memory_limit 128M
  php_value post_max_size 16M
  php_value upload_max_filesize 2M
  php_value max_input_time 300
  php_value always_populate_raw_post_data -1
  # php_value date.timezone Asia/Seoul # <-
</IfModule>
```

```
<IfModule mod_php7.c>
    php_value max_execution_time 300
    php_value memory_limit 128M
    php_value post_max_size 16M
    php_value upload_max_filesize 2M
    php_value max_input_time 300
    # php_value date.timezone Asia/Seoul      # <-
</IfModule>
```

MySQL /

```
root@mon:~# apt-get install mysql-server
root@mon:~# mysql -p -e "CREATE DATABASE zabbix CHARACTER SET utf8 COLLATE
utf8_bin"
root@mon:~# mysql -p -e "grant all on zabbix.* to 'zabbix'@'localhost'
identified by 'SECRETPASSWORD'"
```

mysql client

```
MariaDB [(none)]> CREATE USER 'zabbix'@'localhost' IDENTIFIED BY
'<PASSWORD>';
MariaDB [(none)]> CREATE DATABASE zabbix CHARACTER SET utf8 COLLATE
utf8_bin;
MariaDB [(none)]> GRANT ALL PRIVILEGES ON `zabbix`.* TO
'zabbix'@'localhost';
MariaDB [(none)]> FLUSH PRIVILEGES;
```

DB Table

```
root@mon:~# zcat /usr/share/doc/zabbix-server-mysql/create.sql.gz | mysql -
uzabbix -p zabbix
```

Zabbix Server

/etc/zabbix/zabbix_server.conf

MySQL DB

```
DBName=zabbix
DBUser=zabbix
DBPassword=<PASSWORD>
```

Zabbix Agent

```
root@mon:~# apt install zabbix-agent
```

- <https://www.zabbix.com/documentation/current/manual/quickstart/login>

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/zabbix_install_on_debian_11

Last update: **2021/09/18 04:16**

